

# Product data sheet

Specifications



3 Socket-outlet, New Unica, 2P + E, 16A, French, shutter, screwless terminals, IP3x, glossy, antibacterial, green

NU307906

## Main

|                             |                |
|-----------------------------|----------------|
| Range                       | New Unica      |
| Product or component type   | Socket-outlet  |
| Device presentation         | Mechanism      |
| Device mounting             | Flush          |
| Socket number               | 3              |
| Outlet poles configuration  | 2P + E         |
| Outlet standard             | French         |
| Outlet standard description | Pin earth      |
| Ground lug position         | 45° ground lug |
| Rated current               | 16 A           |

## Complementary

|                                |   |
|--------------------------------|---|
| Device application             | Power supply  |
| Cover type                     | With shutter  |
| [Ue] rated operational voltage | 250 V   |
| Network type                   | AC  |
| Network frequency              | 50/60 Hz  |
| Number of modules              | 6 modules   |
| Fixing mode                    | Clip-in   |
| Colour tint                    | Green   |
| Connections - terminals        | Screwless terminals   |
| Cable cross section            | 0...2.5 mm <sup>2</sup> cable(s), 2 - cable stiffness: flexible<br>0...2.5 mm <sup>2</sup> cable(s), 2 - cable stiffness: rigid |
| Minimum load breaking capacity | 100 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos phi = 0.6   |
| Electrical durability          | 10000 cycles, cos phi = 0.8   |
| Insulation resistance          | > 5 MOhm at 500 V   |
| Dielectric strength            | 2000 V  |
| Material                       | PC: mechanism cover   |
| Surface finish                 | Glossy  |

|                                      |   |
|--------------------------------------|---|
| <b>Quantity per set</b>              | Set of 1 without packaging  |
| <b>Standards</b>                     | IEC 60884-1<br>NF C 61-314  |
| <b>Product certifications</b>        | NF  |
| <b>Embedding depth</b>               | 30 mm   |
| <b>Depth</b>                         | 39.4 mm   |
| <b>Width</b>                         | 45 mm   |
| <b>Height</b>                        | 135 mm  |
| <b>Net weight</b>                    | 0.106 kg  |
| <b>Surface treatment</b>             | Antibacterial   |
| <b>Resistance to chemical agents</b> | Resistant to alcohol (70 %)<br>Resistant to alcohol (96 %)<br>Resistant to A-Lactic Acid<br>Resistant to diluted quaternary ammonium<br>Resistant to diluted bleach<br>Resistant to diluted ammonia<br>Resistant to soapy water<br>Resistant to crystal cleaner<br>Resistant to hydrogen peroxide 10 volumes<br>Resistant to hexane |

## Environment

|  |   |
|--|---|
| <b>Ambient air temperature for operation</b> | -5...35 °C  |
| <b>Ambient air temperature for storage</b>   | -5...50 °C  |
| <b>IK degree of protection</b>               | IK04  |
| <b>IP degree of protection</b>               | IP3x  |
| <b>Environmental characteristic</b>          | Acetone<br>Bleach<br>UV resistant<br>Petrol<br>Oil<br>Alcohol<br>Window-cleaning fluid<br>Liquid soap |

## Packing Units

|                                     |          |
|-------------------------------------|----------|
| <b>Unit Type of Package 1</b>       | PCE      |
| <b>Number of Units in Package 1</b> | 1        |
| <b>Package 1 Height</b>             | 4.0 cm   |
| <b>Package 1 Width</b>              | 4.5 cm   |
| <b>Package 1 Length</b>             | 13.5 cm  |
| <b>Package 1 Weight</b>             | 106.0 g  |
| <b>Unit Type of Package 2</b>       | BB1      |
| <b>Number of Units in Package 2</b> | 10       |
| <b>Package 2 Height</b>             | 12.5 cm  |
| <b>Package 2 Width</b>              | 18.0 cm  |
| <b>Package 2 Length</b>             | 26.0 cm  |
| <b>Package 2 Weight</b>             | 1.174 kg |
| <b>Unit Type of Package 3</b>       | S02      |
| <b>Number of Units in Package 3</b> | 20       |
| <b>Package 3 Height</b>             | 15.0 cm  |

|                         |          |
|-------------------------|----------|
| <b>Package 3 Width</b>  | 30.0 cm  |
| <b>Package 3 Length</b> | 40.0 cm  |
| <b>Package 3 Weight</b> | 2.675 kg |

## Offer Sustainability

|   |   |
|---|---|
| <b>REACH Regulation</b>                               | <a href="#">REACH Declaration</a>   |
| <b>EU RoHS Directive</b>                              | Compliant with Exemptions   |
| <b>Mercury free</b>                                   | Yes   |
| <b>China RoHS Regulation</b>                          | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| <b>RoHS exemption information</b>                     | Yes   |
| <b>Circularity Profile</b>                            | No need of specific recycling operations  |
| <b>WEEE</b>   | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| <b>Minimum percentage of recycled plastic content</b> | 63  |

## Recommended replacement(s)