

Product data sheet

Specifications



2 Socket-outlet, New Unica, complete product, 2P + E, 16A, French, with shutter, IP4X, glossy, untreated, white

NU406918

Main

Range	New Unica
Product or component type	Socket-outlet
Aesthetic name	Unica Pro
Device presentation	Complete product
Device mounting	Flush
Socket number	2
Outlet poles configuration	2P + E
Outlet standard	French
Outlet standard description	Pin earth
Rated current	16 A

Complementary

Device application	Power supply
Cover type	With shutter
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Fixing mode	Screws
Colour tint	White (RAL 9003)
Connections - terminals	Screw terminals
Cable cross section	0...2.5 mm ² cable(s), 2 - cable stiffness: flexible 0...2.5 mm ² cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 I _n and 1.1 I _{un} , cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	PC: mechanism cover
Surface finish	Glossy
Quantity per set	Set of 1 flow-pack
Standards	IEC 60884-1

Product certifications	NF
Embedding depth	24 mm
Depth	47 mm
Width	85 mm
Height	125 mm
Net weight	0.099 kg
Surface treatment	Untreated
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

Ambient air temperature for operation	-5...35 °C
Ambient air temperature for storage	-5...50 °C
IK degree of protection	IK04
IP degree of protection	IP4X
Environmental characteristic	Acetone Bleach UV resistant Petrol Oil Alcohol Window-cleaning fluid Liquid soap

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.7 cm
Package 1 Width	8.5 cm
Package 1 Length	12.6 cm
Package 1 Weight	111 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	12.5 cm
Package 2 Width	18 cm
Package 2 Length	26 cm
Package 2 Weight	690 g
Unit Type of Package 3	S04
Number of Units in Package 3	45
Package 3 Height	30 cm
Package 3 Width	40 cm
Package 3 Length	60 cm

Package 3 Weight 6.983 kg

Offer Sustainability

REACH Regulation [REACH Declaration](#)

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Toxic heavy metal free Yes

Mercury free Yes

China RoHS Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

RoHS exemption information [Yes](#)

Circularity Profile No need of specific recycling operations

WEEE The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)