

# Product data sheet

Specifications



Socket-outlet, New Unica, mechanism with fixing frame, 2P, 16A, European, with shutter, IP4X, painted, anthracite

NU503354

## Main

Range	New Unica
Product or component type	Socket-outlet
Device presentation	Mechanism with zamak fixing frame
Device mounting	Flush
Socket number	1
Outlet poles configuration	2P
Outlet standard	European
Rated current	16 A

## Complementary

Device application	Power supply
Cover type	With shutter
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Number of modules	2 modules
Fixing mode	Screws or claws
Colour tint	Anthracite (RAL 7021)
Connections - terminals	Screw terminals
Cable cross section	0...4 mm <sup>2</sup> cable(s), 2 - cable stiffness: flexible 0...4 mm <sup>2</sup> cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	PC: mechanism cover PC (polycarbonate) GF10 FR: casing CuZn37: terminals Zamak: fixing frame
Surface finish	Painted
Quantity per set	Set of 1 flow-pack

<b>Standards</b>	IEC 60884-1 UNE 20315-1-1 UNE 20315-1-2 NF C 61-314
<b>Product certifications</b>	AENOR EAC NF
<b>Embedding depth</b>	27.5 mm
<b>Depth</b>	37 mm
<b>Width</b>	74.5 mm
<b>Height</b>	74.5 mm
<b>Net weight</b>	0.0615 kg
<b>Surface treatment</b>	Painted
<b>Resistance to chemical agents</b>	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

<b>Ambient air temperature for operation</b>	-5...35 °C
<b>Ambient air temperature for storage</b>	-5...50 °C
<b>IK degree of protection</b>	IK04
<b>IP degree of protection</b>	IP4X
<b>Environmental characteristic</b>	Acetone Bleach UV resistant Petrol Oil Alcohol Window-cleaning fluid Liquid soap

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	4.000 cm
<b>Package 1 Width</b>	7.500 cm
<b>Package 1 Length</b>	7.500 cm
<b>Package 1 Weight</b>	63.000 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	8.000 cm
<b>Package 2 Width</b>	20.000 cm
<b>Package 2 Length</b>	22.500 cm
<b>Package 2 Weight</b>	733.000 g
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	160
<b>Package 3 Height</b>	75.000 cm

---

<b>Package 3 Width</b>	80.000 cm
<b>Package 3 Length</b>	60.000 cm
<b>Package 3 Weight</b>	23.424 kg

---

## Offer Sustainability

---

<b>EU RoHS Directive</b>	Under investigation
<b>Circularity Profile</b>	No need of specific recycling operations
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>Minimum percentage of recycled plastic content</b>	55

---

## Recommended replacement(s)