

Product data sheet

Specifications



Socket-outlet, New Unica, mechanism with fixing frame, 2P + E, 16A, Schuko, with shutter, glossy, untreated, beige

NU503744TA

Main

| | |
|-------------------------------|-----------------------------------|
| Range | New Unica |
| Product or component type | Socket-outlet |
| Device presentation | Mechanism with zamak fixing frame |
| Device mounting | Flush |
| Socket number | 1 |
| Outlet poles configuration | 2P + E |
| Outlet standard | Schuko |
| Outlet standard description | Side earth |
| Socket additional information | With hinged lid |
| Rated current | 16 A |

Complementary

| | |
|--------------------------------|---|
| Device application | Power supply |
| Cover type | With shutter |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Number of modules | 2 modules |
| Fixing mode | Screws or claws |
| Colour tint | Beige (RAL 1013) |
| Connections - terminals | Screw terminals |
| Cable cross section | 0...4 mm ² cable(s), 2 - cable stiffness: flexible 0...4 mm ² cable(s), 2 - cable stiffness: rigid |
| Minimum load breaking capacity | 100 operations 1.25 I _n and 1.1 U _n , cos phi = 0.6 |
| Electrical durability | 10000 cycles, cos phi = 0.8 |
| Insulation resistance | > 5 MOhm at 500 V |
| Dielectric strength | 2000 V |
| Material | PC: mechanism cover PC (polycarbonate) GF10 FR: casing Zamak: fixing frame |
| Surface finish | Glossy |

| | |
|--------------------------------------|---|
| Quantity per set | Set of 1 flow-pack |
| Standards | IEC 60884-1 UNE 20315-1-1 UNE 20315-1-2 DIN VDE 0620-1 |
| Product certifications | EAC AENOR |
| Embedding depth | 30.5 mm |
| Depth | 50 mm |
| Width | 74.5 mm |
| Height | 74.5 mm |
| Net weight | 0.0715 kg |
| Surface treatment | Untreated |
| Resistance to chemical agents | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |

Environment

| | |
|--|---|
| Ambient air temperature for operation | -5...35 °C |
| Ambient air temperature for storage | -5...50 °C |
| IK degree of protection | IK04 |
| IP degree of protection | IP21D |
| Environmental characteristic | Acetone Bleach UV resistant Petrol Oil Alcohol Window-cleaning fluid Liquid soap |

Packing Units

| | |
|-------------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.5 cm |
| Package 1 Width | 4.5 cm |
| Package 1 Length | 5 cm |
| Package 1 Weight | 38 g |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 8.2 cm |
| Package 2 Width | 19.7 cm |
| Package 2 Length | 22.6 cm |
| Package 2 Weight | 485 g |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 50 |

| | |
|------------------|----------|
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 2.863 kg |

Offer Sustainability

| | |
|--|---|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| RoHS exemption information | Yes |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Minimum percentage of recycled plastic content | 46 |

Recommended replacement(s)