

Product data sheet

Specifications



Double socket outlet, New Unica, 2P +E, 16A CZ SK, white

NU206518

Main

Range	New Unica
Product or component type	Socket-outlet
Device presentation	Complete mechanism
Device mounting	Flush
Socket number	2
Outlet poles configuration	2P + E
Outlet standard	Czech Republic
Outlet standard description	Pin earth
Socket additional information	Pin earth
Rated current	16 A

Complementary

Device application	Power supply
Cover type	With shutter
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Fixing mode	2 fixing points
Colour tint	White (RAL 9003)
Connections - terminals	Screw terminals
Cable cross section	0...4 mm ² cable(s), 2 - cable stiffness: flexible 0...4 mm ² - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 I _n and 1.1 U _n , cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	ASA + PC: mechanism cover ABS (acrylonitrile butadiene-styrene): cover frame
Surface finish	Glossy
Quantity per set	Set of 1 flow-pack

Standards	IEC 60884-1
Embedding depth	27 mm
Depth	35.3 mm
Width	85 mm
Height	125 mm
Net weight	0.0864 kg
Surface treatment	Untreated
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

Ambient air temperature for operation	-5...35 °C
Ambient air temperature for storage	-5...50 °C
IK degree of protection	IK01
IP degree of protection	IP21D
Environmental characteristic	Alcohol Bleach Liquid soap Acetone Window-cleaning fluid UV resistant Petrol Oil

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.8 cm
Package 1 Width	8.4 cm
Package 1 Length	12.5 cm
Package 1 Weight	86.4 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	13.7 cm
Package 2 Width	10.3 cm
Package 2 Length	19.3 cm
Package 2 Weight	488 g
Unit Type of Package 3	S04
Number of Units in Package 3	90
Package 3 Height	30 cm
Package 3 Width	40 cm
Package 3 Length	60 cm
Package 3 Weight	9.487 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Recommended replacement(s)