

# Product data sheet

Specifications



## Double socket outlet, New Unica, 2P +E, 16A CZ SK, aluminium

NU206530

### Main

Range	New Unica
Product or component type	Socket-outlet
Device presentation	Complete mechanism
Device mounting	Flush
Socket number	2
Outlet poles configuration	2P + E
Outlet standard	Czech Republic Slovakia
Outlet standard description	Pin earth
Socket additional information	Pin earth
Rated current	16 A

### Complementary

Device application	Power supply
Cover type	With shutter
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Fixing mode	2 fixing points
Colour tint	Aluminium
Connections - terminals	Screw terminals
Cable cross section	0...4 mm <sup>2</sup> cable(s), 2 - cable stiffness: flexible 0...4 mm <sup>2</sup> - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	ASA + PC: mechanism cover ABS (acrylonitrile butadiene-styrene): cover frame
Surface finish	Painted
Quantity per set	Set of 1 flow-pack

<b>Standards</b>	IEC 60884-1
<b>Embedding depth</b>	27 mm
<b>Depth</b>	35.3 mm
<b>Width</b>	85 mm
<b>Height</b>	125 mm
<b>Net weight</b>	0.0864 kg
<b>Surface treatment</b>	Painted
<b>Resistance to chemical agents</b>	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

<b>Ambient air temperature for operation</b>	-5...35 °C
<b>Ambient air temperature for storage</b>	-5...50 °C
<b>IK degree of protection</b>	IK01
<b>IP degree of protection</b>	IP21D
<b>Environmental characteristic</b>	Bleach Liquid soap Oil Petrol Alcohol UV resistant Acetone Window-cleaning fluid

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	3.500 cm
<b>Package 1 Width</b>	8.500 cm
<b>Package 1 Length</b>	12.500 cm
<b>Package 1 Weight</b>	95.000 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	5
<b>Package 2 Height</b>	10.400 cm
<b>Package 2 Width</b>	13.700 cm
<b>Package 2 Length</b>	19.000 cm
<b>Package 2 Weight</b>	536.000 g
<b>Unit Type of Package 3</b>	S04
<b>Number of Units in Package 3</b>	90
<b>Package 3 Height</b>	30.000 cm
<b>Package 3 Width</b>	40.000 cm
<b>Package 3 Length</b>	60.000 cm
<b>Package 3 Weight</b>	10.298 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

### Recommended replacement(s)