


Product data sheet

Specifications



Socket-outlet, New Unica, 2P+E, 16A, Italian, with shutter, beige

NU302344

Main

Range	New Unica
Product or component type	Socket-outlet
Device presentation	Mechanism with central plate
Device mounting	Flush
Socket number	1
Outlet poles configuration	2P + E
Outlet standard	Italian
Outlet standard description	Centred earth
Rated current	16 A

Complementary

Device application	Power supply
Cover type	With shutter
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Number of modules	1 module
Fixing mode	Clip-in
Colour tint	Beige (RAL 1013)
Connections - terminals	Screw terminals
Cable cross section	0...4 mm ² cable(s), 2 - cable stiffness: flexible 0...4 mm ² - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 I _n and 1.1 U _n , cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	PC: mechanism cover PC (polycarbonate) GF10 FR: casing
Surface finish	Glossy
Quantity per set	Set of 1 flow-pack

Standards	IEC 60884-1
Embedding depth	24 mm
Depth	35.5 mm
Width	22.5 mm
Height	45 mm
Net weight	0.0275 kg
Surface treatment	Untreated
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

Ambient air temperature for operation	-5...35 °C
Ambient air temperature for storage	-5...50 °C
IK degree of protection	IK01
IP degree of protection	IP21D
Environmental characteristic	Acetone Window-cleaning fluid UV resistant Liquid soap Petrol Alcohol Oil Bleach

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.55 cm
Package 1 Width	2.25 cm
Package 1 Length	4.5 cm
Package 1 Weight	27.5 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	6.5 cm
Package 2 Width	12 cm
Package 2 Length	18.5 cm
Package 2 Weight	343.3 g
Unit Type of Package 3	S03
Number of Units in Package 3	160
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	5.934 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations
Minimum percentage of recycled plastic content	61

Recommended replacement(s)