

# Product data sheet

Specifications



## Socket-outlet, New Unica, 2P, 16A, European, with shutter, 1 module, beige

NU303344

### Main

|                            |                              |
|----------------------------|------------------------------|
| Range                      | New Unica                    |
| Product or component type  | Socket-outlet                |
| Device presentation        | Mechanism with central plate |
| Device mounting            | Flush                        |
| Socket number              | 1                            |
| Outlet poles configuration | 2P                           |
| Outlet standard            | European                     |
| Rated current              | 16 A                         |

### Complementary

|                                |   |
|--------------------------------|---|
| Device application             | Power supply  |
| Cover type                     | With shutter  |
| [Ue] rated operational voltage | 250 V   |
| Network type                   | AC  |
| Network frequency              | 50/60 Hz  |
| Number of modules              | 2 modules   |
| Fixing mode                    | Clip-in   |
| Colour tint                    | Beige (RAL 1013)  |
| Connections - terminals        | Screw terminals   |
| Cable cross section            | 0...4 mm <sup>2</sup> cable(s), 2 - cable stiffness: flexible<br>0...4 mm <sup>2</sup> - cable stiffness: rigid |
| Minimum load breaking capacity | 100 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos phi = 0.6                                       |
| Electrical durability          | 10000 cycles, cos phi = 0.8   |
| Insulation resistance          | > 5 MOhm at 500 V   |
| Dielectric strength            | 2000 V  |
| Material                       | PC: mechanism cover<br>PC (polycarbonate) GF10 FR: casing   |
| Surface finish                 | Glossy  |
| Quantity per set               | Set of 1 flow-pack  |
| Standards                      | IEC 60884-1<br>DIN VDE 0620-1   |

|                                      |   |
|--------------------------------------|---|
| <b>Product certifications</b>        | EAC<br>VDE  |
| <b>Embedding depth</b>               | 27 mm   |
| <b>Depth</b>                         | 37 mm   |
| <b>Width</b>                         | 45 mm   |
| <b>Height</b>                        | 45 mm   |
| <b>Net weight</b>                    | 0.0287 kg   |
| <b>Surface treatment</b>             | Untreated   |
| <b>Resistance to chemical agents</b> | Resistant to alcohol (70 %)<br>Resistant to alcohol (96 %)<br>Resistant to A-Lactic Acid<br>Resistant to diluted quaternary ammonium<br>Resistant to diluted bleach<br>Resistant to diluted ammonia<br>Resistant to soapy water<br>Resistant to crystal cleaner<br>Resistant to hydrogen peroxide 10 volumes<br>Resistant to hexane |

## Environment

|  |   |
|--|---|
| <b>Ambient air temperature for operation</b> | -5...35 °C  |
| <b>Ambient air temperature for storage</b>   | -5...50 °C  |
| <b>IK degree of protection</b>               | IK01  |
| <b>IP degree of protection</b>               | IP4X  |
| <b>Environmental characteristic</b>          | UV resistant<br>Acetone<br>Liquid soap<br>Oil<br>Window-cleaning fluid<br>Petrol<br>Alcohol<br>Bleach |

## Packing Units

|                                     |         |
|-------------------------------------|---------|
| <b>Unit Type of Package 1</b>       | PCE     |
| <b>Number of Units in Package 1</b> | 1       |
| <b>Package 1 Height</b>             | 4 cm    |
| <b>Package 1 Width</b>              | 4.5 cm  |
| <b>Package 1 Length</b>             | 4.5 cm  |
| <b>Package 1 Weight</b>             | 29 g    |
| <b>Unit Type of Package 2</b>       | BB1     |
| <b>Number of Units in Package 2</b> | 10      |
| <b>Package 2 Height</b>             | 8.2 cm  |
| <b>Package 2 Width</b>              | 17.8 cm |
| <b>Package 2 Length</b>             | 24.8 cm |
| <b>Package 2 Weight</b>             | 391.3 g |
| <b>Unit Type of Package 3</b>       | S03     |
| <b>Number of Units in Package 3</b> | 60      |
| <b>Package 3 Height</b>             | 30 cm   |
| <b>Package 3 Width</b>              | 30 cm   |
| <b>Package 3 Length</b>             | 40 cm   |

---

Package 3 Weight 2.789 kg

## Offer Sustainability

---

REACH Regulation [REACH Declaration](#)

---

REACH free of SVHC Yes

---

EU RoHS Directive Compliant  
[EU RoHS Declaration](#)

---

Toxic heavy metal free Yes

---

Mercury free Yes

---

China RoHS Regulation [China RoHS declaration](#)  
Pro-active China RoHS declaration (out of China RoHS legal scope)

---

RoHS exemption information [Yes](#)

---

Circularity Profile No need of specific recycling operations

---

Minimum percentage of recycled plastic content 55

## Recommended replacement(s)