

Product data sheet

Specifications



Socket outlet, New Unica, 2P+E, 16A, Israel, with shutter, 2 modules, anthracite

NU304754

Main

| | |
|-----------------------------|------------------------------|
| Range | New Unica |
| Product or component type | Socket-outlet |
| Device presentation | Mechanism with central plate |
| Device mounting | Flush |
| Socket number | 1 |
| Outlet poles configuration | 2P + E |
| Outlet standard | European |
| Outlet standard description | Displaced earth |
| Rated current | 16 A |

Complementary

| | |
|--------------------------------|---|
| Device application | Power supply |
| Cover type | With shutter |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Number of modules | 2 modules |
| Fixing mode | Clip-in |
| Colour tint | Anthracite (RAL 7021) |
| Connections - terminals | Screw terminals |
| Cable cross section | 0...4 mm ² cable(s), 2 - cable stiffness: flexible 0...4 mm ² - cable stiffness: rigid |
| Minimum load breaking capacity | 100 operations 1.25 I _n and 1.1 U _n , cos phi = 0.6 |
| Electrical durability | 10000 cycles, cos phi = 0.8 |
| Insulation resistance | > 5 MOhm at 500 V |
| Dielectric strength | 2000 V |
| Material | PC: mechanism cover PC (polycarbonate) GF10 FR: casing |
| Surface finish | Painted |
| Quantity per set | Set of 1 flow-pack |

| | |
|--------------------------------------|---|
| Standards | IEC 60884-1 |
| Product certifications | ISI |
| Embedding depth | 30 mm |
| Depth | 40 mm |
| Width | 45 mm |
| Height | 45 mm |
| Net weight | 0.033 kg |
| Surface treatment | Painted |
| Resistance to chemical agents | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |

Environment

| | |
|--|---|
| Ambient air temperature for operation | -5...35 °C |
| Ambient air temperature for storage | -5...50 °C |
| IK degree of protection | IK01 |
| IP degree of protection | IP21D |
| Environmental characteristic | Liquid soap Acetone Alcohol Window-cleaning fluid UV resistant Bleach Oil Petrol |

Packing Units

| | |
|-------------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.05 cm |
| Package 1 Width | 4.5 cm |
| Package 1 Length | 4.5 cm |
| Package 1 Weight | 32.5 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 4.0 cm |
| Package 2 Width | 9.35 cm |
| Package 2 Length | 22.5 cm |
| Package 2 Weight | 373.0 g |
| Unit Type of Package 3 | S01 |
| Number of Units in Package 3 | 30 |
| Package 3 Height | 15.0 cm |
| Package 3 Width | 15.0 cm |
| Package 3 Length | 40.0 cm |

Package 3 Weight 1.319 kg

Offer Sustainability

REACH Regulation [REACH Declaration](#)

REACH free of SVHC Yes

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Toxic heavy metal free Yes

Mercury free Yes

China RoHS Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

RoHS exemption information Yes

Circularity Profile No need of specific recycling operations

Minimum percentage of recycled plastic content 57

Recommended replacement(s)