

# Product data sheet

Specifications



## Double socket outlet, New Unica, American, with shutter, 15A, 3 modules, aluminium

NU306030

### Main

Range	New Unica
Product or component type	Socket-outlet
Device presentation	Mechanism with central plate
Device mounting	Flush
Socket number	2
Outlet poles configuration	2P + E
Outlet standard	American
Outlet standard description	Centred earth
Rated current	15 A

### Complementary

Device application	Power supply
Cover type	With shutter
[Ue] rated operational voltage	127 V
Network type	AC
Network frequency	50/60 Hz
Number of modules	3 modules
Fixing mode	Clip-in
Colour tint	Aluminium
Connections - terminals	Screw terminals
Cable cross section	0...4 mm <sup>2</sup> - cable stiffness: flexible 0...4 mm <sup>2</sup> - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 I <sub>n</sub> and 1.1 I <sub>n</sub> , cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	PC: mechanism cover PC (polycarbonate) GF10 FR: casing
Surface finish	Painted
Quantity per set	Set of 1 flow-pack

<b>Standards</b>	IEC 60884-1
<b>Embedding depth</b>	24 mm
<b>Depth</b>	30 mm
<b>Width</b>	67.5 mm
<b>Height</b>	45 mm
<b>Net weight</b>	0.036 kg
<b>Surface treatment</b>	Painted
<b>Resistance to chemical agents</b>	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

<b>Ambient air temperature for operation</b>	-5...35 °C
<b>Ambient air temperature for storage</b>	-5...50 °C
<b>IK degree of protection</b>	IK01
<b>IP degree of protection</b>	IP20
<b>Environmental characteristic</b>	UV resistant Alcohol Acetone Bleach Liquid soap Window-cleaning fluid Petrol Oil

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	2.95 cm
<b>Package 1 Width</b>	4.5 cm
<b>Package 1 Length</b>	6.75 cm
<b>Package 1 Weight</b>	36 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	5
<b>Package 2 Height</b>	6.5 cm
<b>Package 2 Width</b>	12 cm
<b>Package 2 Length</b>	18.5 cm
<b>Package 2 Weight</b>	248.3 g
<b>Unit Type of Package 3</b>	S01
<b>Number of Units in Package 3</b>	20
<b>Package 3 Height</b>	15 cm
<b>Package 3 Width</b>	15 cm
<b>Package 3 Length</b>	40 cm
<b>Package 3 Weight</b>	1.193 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

### Recommended replacement(s)