

Socket outlet, New Unica, Schuko, 2P+E, 16A, 2 modules, beige

NU503644Z

Main

Range	New Unica
Product or component type	Socket-outlet
Device presentation	Mechanism with fixing frame and central plate
Device mounting	Flush
Socket number	1
Outlet poles configuration	2P + E
Outlet standard	Schuko
Outlet standard description	Side earth
Rated current	16 A

Complementary

Complementary	
Device application	Power supply
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Number of modules	2 modules
Fixing mode	Long claws
Colour tint	Beige (RAL 1013)
Connections - terminals	Screw terminals
Cable cross section	04 mm² cable(s), 2 - cable stiffness: flexible 04 mm² - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	PC: mechanism cover Zamak: fixing frame PC (polycarbonate) GF10 FR: casing
Surface finish	Glossy
Quantity per set	Set of 1 flow-pack
Standards	IEC 60884-1

Product certifications	VDE
Embedding depth	30.5 mm
Depth	40 mm
Width	74.5 mm
Height	74.5 mm
Net weight	0.0739 kg
Surface treatment	Untreated
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

Ambient air temperature for operation	-535 °C
Ambient air temperature for storage	-550 °C
IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	UV resistant Oil Window-cleaning fluid Bleach Alcohol Petrol Acetone Liquid soap

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	7.5 cm
Package 1 Length	7.5 cm
Package 1 Weight	81.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	8.0 cm
Package 2 Width	20.0 cm
Package 2 Length	22.5 cm
Package 2 Weight	923.0 g
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Height	30.0 cm
Package 3 Width	40.0 cm
Package 3 Length	60.0 cm

Package 3 Weight 11.731 kg

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations
Minimum percentage of recycled plastic content	57

Recommended replacement(s)