

# Product data sheet

Specifications



Socket outlet, New Unica, French, with shutter, 2P+E, 16A, 2 modules, beige

NU303944E

## Main

|                             |                              |
|-----------------------------|------------------------------|
| Range                       | New Unica                    |
| Product or component type   | Socket-outlet                |
| Device presentation         | Mechanism with central plate |
| Device mounting             | Flush                        |
| Socket number               | 1                            |
| Outlet poles configuration  | 2P + E                       |
| Outlet standard             | French                       |
| Outlet standard description | Pin earth                    |
| Ground lug position         | 90° ground lug               |
| Rated current               | 16 A                         |

## Complementary

|                                |   |
|--------------------------------|---|
| Device application             | Power supply  |
| Cover type                     | With shutter  |
| [Ue] rated operational voltage | 250 V   |
| Network type                   | AC  |
| Network frequency              | 50/60 Hz  |
| Number of modules              | 2 modules   |
| Fixing mode                    | Clip-in   |
| Colour tint                    | Beige (RAL 1013)  |
| Connections - terminals        | Screw terminals   |
| Cable cross section            | 0...4 mm <sup>2</sup> - cable stiffness: flexible<br>0...4 mm <sup>2</sup> - cable stiffness: rigid |
| Minimum load breaking capacity | 100 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos phi = 0.6                           |
| Electrical durability          | 10000 cycles, cos phi = 0.8   |
| Insulation resistance          | > 5 MOhm at 500 V   |
| Dielectric strength            | 2000 V  |
| Material                       | PC: mechanism cover<br>Zamak: fixing frame<br>PC (polycarbonate) GF10 FR: casing                    |
| Surface finish                 | Glossy  |

|                                      |   |
|--------------------------------------|---|
| <b>Quantity per set</b>              | Set of 1 flow-pack  |
| <b>Standards</b>                     | IEC 60884-1<br>UNE 20315-1-1<br>UNE 20315-1-2<br>NF C 61-314  |
| <b>Product certifications</b>        | AENOR<br>NF   |
| <b>Embedding depth</b>               | 27 mm   |
| <b>Depth</b>                         | 37 mm   |
| <b>Width</b>                         | 45 mm   |
| <b>Height</b>                        | 45 mm   |
| <b>Net weight</b>                    | 0.0362 kg   |
| <b>Surface treatment</b>             | Untreated   |
| <b>Resistance to chemical agents</b> | Resistant to alcohol (70 %)<br>Resistant to alcohol (96 %)<br>Resistant to A-Lactic Acid<br>Resistant to diluted quaternary ammonium<br>Resistant to diluted bleach<br>Resistant to diluted ammonia<br>Resistant to soapy water<br>Resistant to crystal cleaner<br>Resistant to hydrogen peroxide 10 volumes<br>Resistant to hexane |

## Environment

|  |   |
|--|---|
| <b>Ambient air temperature for operation</b> | -5...35 °C  |
| <b>Ambient air temperature for storage</b>   | -5...50 °C  |
| <b>IK degree of protection</b>               | IK01  |
| <b>IP degree of protection</b>               | IP20  |
| <b>Environmental characteristic</b>          | Bleach<br>Petrol<br>Liquid soap<br>Alcohol<br>Window-cleaning fluid<br>UV resistant<br>Acetone<br>Oil |

## Packing Units

|                                     |         |
|-------------------------------------|---------|
| <b>Unit Type of Package 1</b>       | PCE     |
| <b>Number of Units in Package 1</b> | 1       |
| <b>Package 1 Height</b>             | 4.0 cm  |
| <b>Package 1 Width</b>              | 4.5 cm  |
| <b>Package 1 Length</b>             | 4.5 cm  |
| <b>Package 1 Weight</b>             | 34.0 g  |
| <b>Unit Type of Package 2</b>       | BB1     |
| <b>Number of Units in Package 2</b> | 10      |
| <b>Package 2 Height</b>             | 6.0 cm  |
| <b>Package 2 Width</b>              | 14.0 cm |
| <b>Package 2 Length</b>             | 26.0 cm |
| <b>Package 2 Weight</b>             | 408.0 g |
| <b>Unit Type of Package 3</b>       | S04     |
| <b>Number of Units in Package 3</b> | 240     |

|                  |          |
|------------------|----------|
| Package 3 Height | 30.0 cm  |
| Package 3 Width  | 40.0 cm  |
| Package 3 Length | 60.0 cm  |
| Package 3 Weight | 10.44 kg |

## Offer Sustainability

|  |   |
|--|---|
| REACH Regulation                               | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive                              | Compliant with Exemptions   |
| Mercury free                                   | Yes   |
| China RoHS Regulation                          | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information                     | Yes   |
| Circularity Profile                            | No need of specific recycling operations  |
| Minimum percentage of recycled plastic content | 45  |

## Recommended replacement(s)