

Product data sheet

Specifications



2 Socket-outlet, New Unica, mechanism, 2P + E, 16A, Schuko, with shutter, screw terminal, glossy, antibacterial, white

NU306720A

Main

Range	New Unica
Product or component type	Socket-outlet
Device presentation	Mechanism
Device mounting	Flush
Socket number	2
Outlet poles configuration	2P + E
Outlet standard	Schuko
Outlet standard description	Side earth
Rated current	16 A

Complementary

Device application	Power supply
Cover type	With shutter
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Number of modules	4 modules
Fixing mode	Clip-in
Colour tint	White (RAL 9003)
Connections - terminals	IPT (Isolates Piercing Terminal) Screw terminal
Cable cross section	0...2.5 mm² cable(s), 2 - cable stiffness: flexible 0...2.5 mm² cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	PC: mechanism cover PC (polycarbonate) GF10 FR: casing
Surface finish	Glossy
Quantity per set	Set of 1 flow-pack

Standards	IEC 60884-1 UNE 20315-1-1 UNE 20315-1-2
Product certifications	AENOR
Embedding depth	31.1 mm
Depth	40.4 mm
Width	45 mm
Height	90 mm
Net weight	0.077 kg
Surface treatment	Antibacterial
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

Ambient air temperature for operation	-5...35 °C
Ambient air temperature for storage	-5...50 °C
IK degree of protection	IK01
IP degree of protection	IP21D
Environmental characteristic	Acetone Bleach UV resistant Petrol Oil Alcohol Window-cleaning fluid Liquid soap

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	4.5 cm
Package 1 Length	9 cm
Package 1 Weight	79 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	7.5 cm
Package 2 Width	21.5 cm
Package 2 Length	27 cm
Package 2 Weight	935 g
Unit Type of Package 3	S04
Number of Units in Package 3	90
Package 3 Height	30 cm
Package 3 Width	40 cm

Package 3 Length	60 cm
Package 3 Weight	9.118 kg
Offer Sustainability	
EU RoHS Directive	Under investigation
Circularity Profile	No need of specific recycling operations
Minimum percentage of recycled plastic content	53

Recommended replacement(s)