

Product data sheet

Specifications



2 Socket-outlet, New Unica, mechanism with fixing frame, 2P, 10A, European, with shutter, IP3x, painted, aluminium

NU503130

⚠ Discontinued

⚠ Discontinued on: 30 June 2023

Main

| | |
|----------------------------|-----------------------------------|
| Range | New Unica |
| Product or component type | Socket-outlet |
| Device presentation | Mechanism with zamak fixing frame |
| Device mounting | Flush |
| Socket number | 2 |
| Outlet poles configuration | 2P |
| Outlet standard | European |
| Rated current | 10 A |

Complementary

| | |
|--------------------------------|---|
| Device application | Power supply |
| Cover type | With shutter |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Number of modules | 2 modules |
| Fixing mode | Screws or claws |
| Colour tint | Aluminium |
| Connections - terminals | Screw terminals |
| Cable cross section | 0...4 mm ² cable(s), 2 - cable stiffness: flexible 0...4 mm ² cable(s), 2 - cable stiffness: rigid |
| Minimum load breaking capacity | 100 operations 1.25 I _n and 1.1 U _n , cos phi = 0.6 |
| Electrical durability | 10000 cycles, cos phi = 0.8 |
| Insulation resistance | > 5 MOhm at 500 V |
| Dielectric strength | 2000 V |
| Material | PC: mechanism cover PC (polycarbonate) GF10 FR: casing CuZn37: terminals Zamak: fixing frame |
| Surface finish | Painted |

| | |
|--------------------------------------|---|
| Quantity per set | Set of 1 flow-pack |
| Standards | IEC 60884-1 UNE 20315-1-1:1994 |
| Product certifications | EAC |
| Embedding depth | 30 mm |
| Depth | 39.3 mm |
| Width | 74.5 mm |
| Height | 74.5 mm |
| Net weight | 0.0715 kg |
| Surface treatment | Painted |
| Resistance to chemical agents | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |

Environment

| | |
|--|---|
| Ambient air temperature for operation | -5...35 °C |
| Ambient air temperature for storage | -5...50 °C |
| IK degree of protection | IK04 |
| IP degree of protection | IP3x |
| Environmental characteristic | Acetone Bleach UV resistant Petrol Oil Alcohol Window-cleaning fluid Liquid soap |

Packing Units

| | |
|-------------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.5 cm |
| Package 1 Width | 7.5 cm |
| Package 1 Length | 4 cm |
| Package 1 Weight | 72 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 15 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 1144 g |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 160 |
| Package 3 Height | 77 cm |

| | |
|-------------------------|---------|
| Package 3 Width | 80 cm |
| Package 3 Length | 60 cm |
| Package 3 Weight | 26804 g |

Offer Sustainability

| | |
|---|--|
| EU RoHS Directive | Under investigation |
| Circularity Profile | No need of specific recycling operations |
| Minimum percentage of recycled plastic content | 60 |

Recommended replacement(s)