

# Product data sheet

Specifications



## One way switch, New Unica, 10 A, with studio frame, aluminium

NU220130D

### Main

Range of product	New Unica
Product or component type	Switch
Device presentation	Complete product
Technology type	Electromechanical
Switch function	1-pole 1-way
Number of rocker	1
Device application	Light control
Colour tint	Aluminium Cream
Type of packing	Flow-pack

### Complementary

Rated current	10 A 10 AX
[Ue] rated operational voltage	250 V 250 V
Network type	AC AC
Network frequency	50/60 Hz 50/60 Hz
Electrical durability	10000 cycles 20000 cycles, cos phi = 0.6
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi = 0.3
Condition of use	Indoor
Opening distance	> 3 mm
Actuator	Rocker
Number of modules	2 modules
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm <sup>2</sup> rigid cable 0...2.5 mm <sup>2</sup> flexible cable
Material	ABS (acrylonitrile butadiene-styrene): cover frame ABS (acrylonitrile butadiene-styrene): mechanism cover

Surface finish	Glossy
Specific treatment - integrated within the material	Painted
Fixing mode	Long claws
Width	85 mm
Height	85 mm
Depth	34.25 mm
Embedding depth	21.15 mm
Net weight	0.054 kg
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-5...50 °C
Standards	EN 60669-1 LV directive EMC directive
Product certifications	CE AENOR EAC NF VDE
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

IP degree of protection	IP4X
IK degree of protection	IK04
Environmental characteristic	Window-cleaning fluid Oil Bleach Liquid soap Acetone Petrol Alcohol UV resistant

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 cm
Package 1 Width	8.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	66 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	12 cm
Package 2 Width	17.5 cm
Package 2 Length	26 cm
Package 2 Weight	795 g

<b>Unit Type of Package 3</b>	S04
<b>Number of Units in Package 3</b>	80
<b>Package 3 Height</b>	30 cm
<b>Package 3 Width</b>	40 cm
<b>Package 3 Length</b>	60 cm
<b>Package 3 Weight</b>	7.063 kg

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>REACH free of SVHC</b>	Yes
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Toxic heavy metal free</b>	Yes
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>Circularity Profile</b>	No need of specific recycling operations

## Recommended replacement(s)