

Product data sheet

Specifications



Pushbutton switch, New Unica, 10 A, with studio frame, white

NU220618D

Main

Range of product	New Unica
Product or component type	Push-button
Device presentation	Complete product
Technology type	Electromechanical
Number of rocker	1
Device application	Light control
Colour tint	White (RAL 9003)
Type of packing	Flow-pack

Complementary

Rated current	10 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Electrical durability	40000 cycles, cos phi = 0.6 20000 cycles, cos phi = 0.6
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi = 0.3
Condition of use	Indoor
Opening distance	> 3 mm
Actuator	Rocker
Number of modules	2 modules
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm ² rigid cable 0...2.5 mm ² flexible cable
Material	ASA + PC: cover frame ABS (acrylonitrile butadiene-styrene): cover frame ABS (acrylonitrile butadiene-styrene): mechanism cover ASA + PC: mechanism cover
Surface finish	Glossy

Specific treatment - integrated within the material	Untreated
Fixing mode	Long claws
Width	85 mm
Height	85 mm
Depth	34.25 mm
Embedding depth	21.15 mm
Net weight	0.0537 kg
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-5...50 °C
Standards	EN 60669-1 LV directive EMC directive
Product certifications	CE AENOR EAC NF VDE

Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane
--------------------------------------	---

Environment

IP degree of protection	IP4X
IK degree of protection	IK04
Environmental characteristic	Acetone Oil Window-cleaning fluid UV resistant Alcohol Petrol Liquid soap Bleach

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	8.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	65.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	12.0 cm
Package 2 Width	17.5 cm
Package 2 Length	26.0 cm
Package 2 Weight	785.0 g
Unit Type of Package 3	S02

Number of Units in Package 3	20
Package 3 Height	15.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	1.885 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations

Recommended replacement(s)