

Product data sheet

Specifications



Push button switch, New Unica, location lamp, 10 A, 2 module, beige

NU320644N

Main

| | |
|---------------------------|-------------------|
| Range of product | New Unica |
| Product or component type | Push-button |
| Device presentation | Mechanism |
| Technology type | Electromechanical |
| Number of rocker | 1 |
| Device application | Light control |
| Provided equipment | LED |
| Colour tint | Beige (RAL 1013) |
| Type of packing | Flow-pack |

Complementary

| | |
|--------------------------------|---|
| Rated current | 10 A |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Electrical durability | 40000 cycles, cos phi = 0.6 20000 cycles, cos phi = 0.6 |
| Insulation resistance | > 5 MOhm at 500 V |
| Dielectric strength | 2000 V |
| Minimum load breaking capacity | 200 operations 1.25 In and 1.1 Un, cos phi = 0.3 |
| Condition of use | Indoor |
| Opening distance | > 3 mm |
| Actuator | Rocker |
| Number of modules | 2 modules |
| Pilot light | LED, colour: blue, current consumption: 0.15 mA, temperature rise: 15 °C LED, colour: white, current consumption: 0.05 mA, temperature rise: 15 °C |
| Connections - terminals | Screwless terminals |
| Cable cross section | 0...2.5 mm ² rigid cable 0...2.5 mm ² flexible cable |
| Material | ASA + PC: mechanism cover ABS (acrylonitrile butadiene-styrene): mechanism cover |

| | |
|--|---|
| Marking | OFF |
| Surface finish | Glossy |
| Specific treatment - integrated within the material | Untreated |
| Fixing mode | Clip-in |
| Width | 45 mm |
| Height | 45 mm |
| Depth | 34.25 mm |
| Embedding depth | 21.15 mm |
| Net weight | 0.0226 kg |
| Ambient air temperature for operation | -5...40 °C |
| Ambient air temperature for storage | -5...50 °C |
| Standards | EN 60669-1 LV directive EMC directive |
| Product certifications | CE AENOR EAC NF VDE |
| Resistance to chemical agents | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |

Environment

| | |
|-------------------------------------|---|
| IP degree of protection | IP4X |
| IK degree of protection | IK04 |
| Environmental characteristic | Acetone Bleach Petrol Window-cleaning fluid Liquid soap Oil UV resistant Alcohol |

Packing Units

| | |
|-------------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.500 cm |
| Package 1 Width | 4.500 cm |
| Package 1 Length | 4.500 cm |
| Package 1 Weight | 26.000 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 8.000 cm |
| Package 2 Width | 18.000 cm |
| Package 2 Length | 18.500 cm |

| | |
|------------------------------|-----------|
| Package 2 Weight | 347.000 g |
| Unit Type of Package 3 | S02 |
| Number of Units in Package 3 | 20 |
| Package 3 Height | 15.000 cm |
| Package 3 Width | 30.000 cm |
| Package 3 Length | 40.000 cm |
| Package 3 Weight | 945.000 g |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| RoHS exemption information | Yes |
| Circularity Profile | No need of specific recycling operations |

Recommended replacement(s)