

#### Main

Range	New Unica
Product or component type	Telephone socket
Device application	Communication
Device presentation	Mechanism
Colour tint	Anthracite (RAL 7021)
Telephone socket type	France Telecom (8 contacts)

New Unica - telephone socket - 1

### Complementary

Socket number	1
Number of modules	2 modules
Connections - terminals	Screw terminals
	Screw terminals 4 pairs cable
Fixing mode	Clip-in
Material	Thermoplastic ABS-UV stabilised: centre plate
Depth	36 mm
Width	45 mm
Height	45 mm
Embedding depth	20 mm
Net weight	0.026 kg
Ambient air temperature for operation	545 °C
Ambient air temperature for storage	-550 °C

Resistance to chemical agents

Resistant to alcohol (70 %) Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

_	:			1
-	nvi	ror	m	ent
_		101	,,,,,	<b>-11</b>

IP degree of protection	IP20
IK degree of protection	IK02

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.8 cm
Package 1 Width	7.5 cm
Package 1 Length	7.9 cm
Package 1 Weight	30.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	6.0 cm
Package 2 Width	26.0 cm
Package 2 Length	14.0 cm
Package 2 Weight	351.0 g
Unit Type of Package 3	S01
Number of Units in Package 3	20
Package 3 Height	15.0 cm
Package 3 Width	15.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	912.0 g

## Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
RoHS exemption information	Yes	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

### Recommended replacement(s)