

Telephone socket, New Unica, British, 1 module, beige

NU349944

Range	New Unica
Product or component type	Telephone socket
Device presentation	Mechanism with central plate
Colour tint	Beige Beige (RAL 1013)
Telephone socket type	British (6 contacts) - category 3 at 16 Mbit/s

Complementary

Socket number	1
Number of modules	1 module
Connections - terminals	Screw terminals twisted pair
Device mounting	Flush
Fixing mode	Clip-in
Material	ASA + PC: mechanism cover ABS (acrylonitrile butadiene-styrene) GF10 FR: mechanism cover
Depth	23 mm
Width	22.5 mm
Height	45 mm
Embedding depth	12 mm
Net weight	0.015 kg
Ambient air temperature for operation	-545 °C
Ambient air temperature for storage	-545 °C

Resistance to chemical agents Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

_							
⊢	n١	/1	ro	n	m	0	nt

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Liquid soap Bleach UV resistant Window-cleaning fluid Petrol Oil Acetone Alcohol

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.75 cm
Package 1 Width	2.25 cm
Package 1 Length	4.5 cm
Package 1 Weight	13 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	6.5 cm
Package 2 Width	12 cm
Package 2 Length	18.5 cm
Package 2 Weight	198.3 g
Unit Type of Package 3	S04
Number of Units in Package 3	360
Package 3 Height	30 cm
Package 3 Width	40 cm
Package 3 Length	60 cm
Package 3 Weight	7.842 kg

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Recommended replacement(s)