

Product data sheet

Specifications

Cover frame, Unica Pro, 4 gangs, white



NU400818

Main

Range	New Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Pro
Number of gangs	4 gangs
Installation direction	Horizontal/vertical
Type of frame	Quadruple
Number of modules	4 x 2 modules
Fixing mode	Clip-in
Colour tint	White (RAL 9003)

Complementary

Material	Thermoplastic ABS-UV stabilised: cover frame Polycarbonate: intermediate plate
Standards	IEC 60884-1 IEC 60669-1
Width	298 mm
Height	85 mm
Depth	10 mm
Net weight	0.051 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

IK degree of protection	IK04
IP degree of protection	IP21D

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1 cm
Package 1 Width	8.5 cm
Package 1 Length	30 cm
Package 1 Weight	56 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	7.5 cm
Package 2 Width	9.5 cm
Package 2 Length	32 cm
Package 2 Weight	350 g
Unit Type of Package 3	S03
Number of Units in Package 3	45
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	3.595 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations

Recommended replacement(s)