Cover frame, Unica Pro, 4 gangs, aluminium



NU400830

Range	New Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Pro
Number of gangs	4 gangs
Installation direction	Horizontal/vertical
Type of frame	Quadruple
Number of modules	4 x 2 modules
Fixing mode	Clip-in
Colour tint	Aluminium

Complementary

Material	Thermoplastic ABS-UV stabilised: cover frame Polycarbonate: intermediate plate
Standards	IEC 60669-1 IEC 60884-1
Width	298 mm
Height	85 mm
Depth	10 mm
Net weight	0.051 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium

Environment

IK degree of protection	IK04
IP degree of protection	IP21D

Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hexane

Resistant to hydrogen peroxide 10 volumes

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	29.8 cm
Package 1 Length	1 cm
Package 1 Weight	56 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	7.5 cm
Package 2 Width	9.5 cm
Package 2 Length	32 cm
Package 2 Weight	350 g
Unit Type of Package 3	S03
Number of Units in Package 3	45
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	3.6 kg

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations

Recommended replacement(s)