

Main Range New Unica **Device application** Mounting Product or component type Cover frame Aesthetic name Unica Pure **Number of gangs** 2 gangs Installation direction Horizontal Type of frame Double **Number of modules** 2 x 2 modules Fixing mode Clip-in **Colour tint** Aluminium Side color White (RAL 9003) Complementary

Material	Zamak: cover frame Polycarbonate: intermediate plate
Standards	IEC 60669-1 IEC 60884-1
Width	156 mm
Height	90 mm
Depth	11 mm
Net weight	0.135 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %)

Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection	IK04
IP degree of protection	IP21D

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	9.5 cm
Package 1 Length	19.5 cm
Package 1 Weight	177.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	35
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.635 kg

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations

Recommended replacement(s)