

### Main

Range	New Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Pure
Number of gangs	2 gangs
Installation direction	Vertical
Type of frame	Double
Number of modules	2 x 2 modules
Fixing mode	Clip-in
Colour tint	Black
Side color	Black (RAL 7021)

### Complementary

Material	Zamak: cover frame Polycarbonate: intermediate plate
Standards	IEC 60884-1 IEC 60669-1
Width	85 mm
Height	160 mm
Depth	11 mm
Net weight	0.135 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %)

Resistant to alcohol (96 %)
Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium Resistant to diluted bleach

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

#### **Environment**

IK degree of protection	IK04
IP degree of protection	IP21D

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.6 cm
Package 1 Width	9.6 cm
Package 1 Length	20.0 cm
Package 1 Weight	177.0 g
Unit Type of Package 2	S01
Number of Units in Package 2	6
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	1.26 kg

# Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations

### Recommended replacement(s)