
# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





NU840430

|--|

Range	New Unica
Device application	Mounting
Product or component type	Mounting box
Aesthetic name	Unica Pro
Number of modules	4 modules 2 x 2 modules
Number of gangs	2 gangs
Fixing mode	Screws

### Complementary

Device mounting	Surface
Cable entry	6 knock-outs
Material	ABS (acrylonitrile butadiene-styrene): box
Standards	IEC 60884-1 IEC 60669-1
Depth	40 mm
Width	158 mm
Height	87 mm
Net weight	0.086 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach

Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hexane

Resistant to hydrogen peroxide 10 volumes

## **Environment**

IK degree of protection IK04

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	4.8 cm
Package 1 Width	8.6 cm
Package 1 Length	15.6 cm
Package 1 Weight	83.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	12.4 cm
Package 2 Width	18 cm
Package 2 Length	26 cm
Package 2 Weight	546 g
Unit Type of Package 3	S02
Number of Units in Package 3	10
Package 3 Height	15 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	1.442 kg

# Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Circularity Profile	No need of specific recycling operations

### Recommended replacement(s)