

Product data sheet

Specifications



Workstation, New Unica, Surface, 2 x 4 modules vertical, aluminium

NU122430

Main

Range	New Unica
Product or component type	Workstation
Number of modules	2 x 4 modules
Mounting position	Vertical
Fixing mode	Screws

Complementary

Provided equipment	Fixing frame Cover frame
Device mounting	Surface
Cable entry	3 removable plates 1 bottom cable entry 20 mm for diameter 1 bottom cable entry 30 mm for diameter 1 bottom cable entry 40 mm for diameter 1 bottom cable entry 25 mm for diameter knock-outs 20 mm for diameter
Material	ABS (acrylonitrile butadiene-styrene): box ABS (acrylonitrile butadiene-styrene): separator ABS (acrylonitrile butadiene-styrene): cover frame
Depth	60 mm
Width	165 mm
Height	165 mm
Net weight	0.379 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

IK degree of protection	IK04
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	18.5 cm
Package 1 Length	18.5 cm
Package 1 Weight	476.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	20
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	10.296 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations

Recommended replacement(s)