

Product data sheet

Specifications



Workstation, New Unica, flush, 2 x 4 modules vertical, white

NU172418

Main

Range	New Unica
Product or component type	Workstation
Number of modules	2 x 4 modules
Mounting position	Vertical
Fixing mode	Embedment Claws

Complementary

Provided equipment	Fixing frame Cover frame
Device mounting	Flush
Cable entry	5 knock-outs 20 mm for diameter 5 knock-outs 25 mm for diameter 2 bottom cable entries 50 x 35 mm for size 20 mm for diameter 2 bottom cable entries 50 x 35 mm for size 25 mm for diameter
Fire resistance	850 °C, extinction time <30 s
Material	ABS (acrylonitrile butadiene-styrene): separator PC: box ABS (acrylonitrile butadiene-styrene): cover frame
Depth	62 mm
Width	165 mm
Height	165 mm
Net weight	0.278 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

IK degree of protection	IK04
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Height	7.9 cm
Package 1 Width	17.9 cm
Package 1 Length	18.6 cm
Package 1 Weight	382.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	20
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	8.663 kg
Unit Type of Package 3	P06
Number of Units in Package 3	80
Package 3 Height	77.0 cm
Package 3 Width	80.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	43.152 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations
Minimum percentage of recycled plastic content	21

Recommended replacement(s)