Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Workstation, New Unica, flush, 4 x 4 modules vertical, anthracite

NU174454

M	a	ın

Range	New Unica
Product or component type	Workstation
Number of modules	4 x 4 modules
Mounting position	Vertical
Fixing mode	Claws Embedment

Complementary

Provided equipment	Cover frame Fixing frame
Device mounting	Flush
Cable entry	4 bottom cable entries 50 x 35 mm for size 25 mm for diameter 8 knock-outs 20 mm for diameter 8 knock-outs 25 mm for diameter 4 bottom cable entries 50 x 35 mm for size 20 mm for diameter
Fire resistance	850 °C, extinction time <30 s
Material	ABS (acrylonitrile butadiene-styrene): separator PC: box ABS (acrylonitrile butadiene-styrene): cover frame
Depth	62 mm
Width	300 mm
Height	165 mm
Net weight	0.514 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach

Environment

IK degree of protection IK04

Packing Units

Unit Type of Package 1 PCE

Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hexane

Resistant to hydrogen peroxide 10 volumes

Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	18.5 cm
Package 1 Length	31.8 cm
Package 1 Weight	660 g
Unit Type of Package 2	S04
Number of Units in Package 2	10
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	7.455 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations
Minimum percentage of recycled plastic content	32

Recommended replacement(s)