

Product data sheet

Specifications



Unica system+ , Pole3S, 2.15m, 4xDE SO+USBA/C+2xC6ASTP-W

INS45102

Main

Range	Unica
Product type	Pole
Type of pole	One-sided
Configuration	Pre-wired, with outlets, cable and plug
Outlet standard	Schuko
Product compatibility	Unica outlet Unica power supply
Quantity package 1 / unit	1

Complementary

Pole/Post surface finish	Powder coated
Fixing mode	Free-standing
Number of power socket outlets	4 at 250 V 16 A side earth
Integrated connection type	RJ45 USB type A, output voltage= 5 V DC at 2.4 A USB type C, output voltage= 5 V DC at 2.4 A
Number of data socket outlets	2 STP
Provided equipment	2 x cable with 6 mm shielded cable cable 1 x cable with 10 mm unshielded cable cable
Clamping connection capacity	3 x 1.5 mm ²
Product material	Aluminium white RAL 9003
Height	2150 mm
Width	70 mm
Depth	70 mm
Shape	I-shape
Adjustment	Vertical: 2000 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.0 cm
Package 1 Width	39.0 cm

Package 1 Length	215.0 cm
Package 1 Weight	10.5 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Recommended replacement(s)