

ELMARK[®]

The Brand of Electricity

RECESSED LED AMBIENT LIGHT



GENERAL INFORMATION »

- ∴ Rated voltage: 85-265VAC
- ∴ Power: 3W
- ∴ Colour temperature: 4000K
- ∴ LED source: SMD
- ∴ Colour: White; Black
- ∴ Body: Aluminium
- ∴ Beam angle: 120°
- ∴ Colour rendering index: Ra≥80
- ∴ Protection against dust and moisture: IP20
- ∴ Sensor type: PIR/Light; Detection distance: max. 2m;
Ambient Light: < 10LUX; Time-Delay: 30s

FEATURES »

- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ Modern luminaire designed for hotels, offices, conference halls, museums.
- ∴ Lightweight construction

PRODUCT DETAILS »

Catalogue number	Watt (W)	Whole fixture lumens (lm)	Lumen efficiency	Colour temp. (K)	Colour body
92EL1460340/WH	3	33	11lm/W	4000	white
92EL1460340/BL	3	16	5.33lm/W	4000	black
92EL1470340/WH	3	30	10lm/W	4000	white
92EL1470340/BL	3	8	8lm/W	4000	black
92EL1480340/WH	3	7	2.33lm/W	4000	white
92EL1480340/BL	3	6	2lm/W	4000	black

DIMENSIONS »

Catalogue number	Length (mm)	Width (mm)	Depth (mm)	Cut size (mm)
92EL1460340/WH	90	40	50	72x38
92EL1460340/BL	90	40	50	72x38
92EL1470340/WH	185	40	50	157x33
92EL1470340/BL	185	40	50	157x33
92EL1480340/WH	86	90	35	80x80
92EL1480340/BL	86	90	35	80x80

