

General Information

Product ID:	1SDA054396R1
EAN:	8015644554941
Catalog Description:	T5N 630 PR221DS-LS/I In=630 3P F F
Long Description:	Automatic moulded case circuit-breaker, SACE Tmax T5, Icu 415 V AC = 36kA, Size Iu = 630A , Electronic trip unit with against overload and as an alternative protection function against delay short circuit or protection against instantaneous short circuit, In = 630A, 3 poles, Version = Fixed, connection terminal = Front terminal

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

Ordering

EAN:	8015644554941
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	140 mm
Product Net Height:	205 mm
Product Net Depth:	103.5 mm
Product Net Weight:	5.1 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	248 mm
Package Level 1 Height:	240 mm
Package Level 1 Length:	285 mm
Package Level 1 Gross Weight:	5.1 kg
Package Level 1 EAN:	8015644554941

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007-01-01
---------------------	--

Additional Information

Electrical Durability:	5000
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Power Loss:	Per Pole 41 W
Product Main Type:	SACE Tmax
Product Name:	T5
Rated Current (I_n):	630 A
Rated Operational Voltage (U_e):	690 V AC
Release Type:	PR221DS-LS/I
Standards:	IEC 60947
Suitable For:	T5
Suitable for Product Class:	Moulded Case Circuit Breakers
Terminal Connection Type:	Fixed Circuit-Breakers
Test Voltage at Industrial Frequency 3500 V for 1 Minute:	
Version:	Fixed

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SDL000158R0033
--	---------------------------------

Classifications

E-number:	3180374
Object Classification Code:	Q
UNSPSC:	39121100

