

# DS951 C20-30MA/AC



Products → Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs  
→ Residual Current Circuit Breakers with Overcurrent Protection RCBO

## General Information

<b>Extended Product Type:</b>	DS951 C20-30MA/AC
<b>Product ID:</b>	16021385
<b>EAN:</b>	8012542413806
<b>Catalog Description:</b>	DS951 C20-30MA/AC- RCBO
<b>Long Description:</b>	The RCBOs DS 951 series has the function to protect in terminal single-phase circuit, against overload and short-circuit currents protection against the effects of sinusoidal alternating earth fault currents protection against indirect contacts and additional protection against direct contacts.

## Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85389099

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	Not available
<b>Instructions and Manuals:</b>	400-9936

## Dimensions

<b>Product Net Width:</b>	0.0356 m
<b>Product Net Height:</b>	0.085 m
<b>Product Net Depth / Length:</b>	0.070 m
<b>Product Net Weight:</b>	0.200 kg

## Technical

<b>Standards:</b>	IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1
<b>Type of Residual Current:</b>	AC type
<b>Rated Residual Current:</b>	30 mA
<b>Tripping Characteristic:</b>	C
<b>Rated Current (I<sub>n</sub>):</b>	20 A
<b>Number of Poles:</b>	2
<b>Number of Protected Poles:</b>	1
<b>Rated Short-Circuit Capacity (I<sub>cn</sub>):</b>	(230 / 400 V AC) 6 kA

<b>Position of Neutral Terminals:</b>	Right
<b>Power Loss:</b>	3 W
<b>Rated Voltage (U<sub>r</sub>):</b>	230-240 V AC

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +55 °C Storage -40 ... +70 °C
<b>RoHS Status:</b>	Following EU Directive 2011/65/EU

## Certificates and Declarations (Document Number)

<b>Declaration of Conformity - CE:</b>	9AKK106713A5599
<b>Environmental Information:</b>	ITSCE-LPD-ENV_DS9
<b>Instructions and Manuals:</b>	400-9936
<b>RoHS Information:</b>	9AKK106713A8874

## Container Information

<b>Package Level 1 Units:</b>	5 piece
<b>Package Level 1 Width:</b>	0.22 m
<b>Package Level 1 Height:</b>	0.082 m
<b>Package Level 1 Depth / Length:</b>	0.093 m
<b>Package Level 1 Gross Weight:</b>	0.908 kg
<b>Package Level 1 EAN:</b>	8012542413813

## Classifications

<b>Object Classification Code:</b>	Q
<b>ETIM 4:</b>	EC000905 - Earth leakage circuit breaker
<b>ETIM 5:</b>	EC000905 - Earth leakage circuit breaker
<b>ETIM 6:</b>	EC000905 - Earth leakage circuit breaker
<b>ETIM 7:</b>	EC000905 - Earth leakage circuit breaker



