



BALAST ELECTRONIC



| Cod | Model | P _(i) | Temp. max de operare | Factor de putere | Utilizare | Dimensiuni L x l x h | Stocabil |
|-------------------|---------------|------------------|----------------------|------------------|-----------------|----------------------|----------|
| unitate de măsură | | W | ° C | | | mm | |
| EL0024480 | TG-4301.12110 | 1 x 10 | max.+70° C | >0.9 | T8 fluorescente | 200 x 25 x 20 | ✓ |
| EL0024103 | TG-4301.12115 | 1 x 15 | max.+70° C | >0.9 | T8 fluorescente | 200 x 25 x 20 | ✓ |
| EL0024104 | TG-4301.12118 | 1 x 18 | max.+70° C | >0.9 | T8 fluorescente | 200 x 25 x 20 | ✓ |
| EL0024105 | TG-4301.12130 | 1 x 30 | max.+70° C | >0.9 | T8 fluorescente | 200 x 25 x 20 | ✓ |
| EL0024106 | TG-4301.12136 | 1 x 36 | max.+70° C | >0.9 | T8 fluorescente | 210 x 30 x 28 | ✓ |
| EL0024107 | TG-4301.12218 | 2 x 18 | max.+70° C | >0.9 | T8 fluorescente | 190 x 32 x 25 | ✓ |
| EL0024108 | TG-4301.12236 | 2 x 36 | max.+70° C | >0.9 | T8 fluorescente | 190 x 32 x 25 | ✓ |
| EL0024109 | TG-4301.12418 | 4 x 18 | max.+70° C | >0.9 | T8 fluorescente | 208 x 38 x 29 | ✓ |
| EL0027248 | TG-4301.12158 | 1 x 58 | max.+70° C | >0.9 | T8 fluorescente | 200 x 20 x 26 | ✓ |
| EL0027249 | TG-4301.12258 | 2 x 58 | max.+70° C | >0.9 | T8 fluorescente | 210 x 30 x 28 | ✓ |
| EL0024340 | TG-4301.42113 | 1 x 13 | max.+70° C | >0.9 | PLC | 200 x 26 x 20 | ✓ |
| EL0024341 | TG-4301.42118 | 1 x 18 | max.+70° C | >0.9 | PLC | 200 x 26 x 20 | ✓ |
| EL0024342 | TG-4301.42126 | 1 x 26 | max.+70° C | >0.9 | PLC | 200 x 26 x 20 | ✓ |
| EL0024343 | TG-4301.42213 | 2 x 13 | max.+70° C | >0.9 | PLC | 192 x 32 x 25 | ✓ |
| EL0024344 | TG-4301.42218 | 2 x 18 | max.+70° C | >0.9 | PLC | 192 x 32 x 25 | ✓ |
| EL0024345 | TG-4301.42226 | 2 x 26 | max.+70° C | >0.9 | PLC | 192 x 32 x 25 | ✓ |

Echipare: bloc terminal



Informații logistice:
vezi indexul de la sfârșitul catalogului