

PHILIPS

Lighting



MASTERColour CDM-TC

MASTERColour CDM-TC 35W/830 G8.5 1CT/12

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light

Product data

General Information		Luminous Efficacy (Rated) (Nom)		79 lm/W	
Cap-Base	G8.5 [G8.5]	Color Rendering Index (Nom)	81		
Operating Position	UNIVERSAL [Any or Universal (U)]	Operating and Electrical			
Life to 5% Failures (Nom)	9000 h	Power (Rated) (Nom)	39.0 W		
Life to 10% Failures (Nom)	10000 h	Lamp Current Run-Up (Max)	0.8 A		
Life to 20% Failures (Nom)	11000 h	Lamp Current (EM) (Nom)	0.53 A		
Life to 50% Failures (Nom)	12000 h	Ignition Supply Voltage (Max)	198 V		
ANSI Code HID	C130/E	Ignition Peak Voltage (Max)	5000 V		
Light Technical		Ignition Supply Voltage (Min)	198 V		
Color Code	830 [CCT of 3000K]	Ignition Peak Voltage (Min)	3500 V		
Luminous Flux (Rated) (Nom)	3000 lm	Re-Ignition Time (Min) (Max)	15 min		
Color Designation	Warm White (WW)	Ignition Time (Max)	30 s		
Lumen Maintenance 10000 h (Nom)	50 %	Voltage (Max)	96 V		
Lumen Maintenance 2000 h (Min)	70 %	Voltage (Min)	80 V		
Lumen Maintenance 2000 h (Nom)	80 %	Voltage (Nom)	88 V		
Lumen Maintenance 5000 h (Min)	50 %	Controls and Dimming			
Lumen Maintenance 5000 h (Nom)	65 %	Dimmable	No		
Chromaticity Coordinate X (Nom)	0.432	Run-Up Time 90% (Max)	3 min		
Chromaticity Coordinate Y (Nom)	0.394				
Correlated Color Temperature (Nom)	3000 K				

MASTERCcolour CDM-TC


Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	UV-Block Quartz
Approval and Application	
Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	3 mg
Energy Consumption kWh/1000 h	43 kWh
UV	
Pet (Niosh) (Min)	8 h/500lx
Damage Factor D/fc (Max)	0.3
Luminaire Design Requirements	
Bulb Temperature (Max)	500 °C

Pinch Temperature (Max)	300 °C
Product Data	
Full product code	871150020000615
Order product name	MASTERCcolour CDM-TC 35W/830 G8.5 1CT/12
EAN/UPC - Product	8711500200006
Order code	928085205125
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928085205125
Net Weight (Piece)	10.000 g
ILCOS Code	MT/UB-35/830-H-G8.5-17/85

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. 35W/830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing






CDM-TC 35W/830 G8.5

Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MASTERCcolour CDM-TC 35W/830 G8.5 1CT/12	15 mm	0.5 in	5 mm	51 mm	53 mm	52 mm	85 mm

MASTERColour CDM-TC



Photometric data



CDM-TC 35W, 70W /830

MASTERColour CDM-TC 35W, 70W /830

Lifetime



CDM-TC 35W Lumen Maintenance /830

CDM-TC 35W, 70W Life Expectancy /830, /842 G8.5

