

# PHILIPS

## Lighting



## Accentline

### Accentline 35W 4000h GU5.3 12V 36D 1CT/10X5F

Low-voltage halogen burner in glass reflector. Ideal solution for small decorative luminaires, putting your objects in the spotlight. Dichroic coating prevents heat transmission onto the object.

#### Product data

##### General Information

Cap-Base	GU5.3 [ GU5.3]
Operating Position	UNIVERSAL [ Any or Universal (U)]
Life to 50% Failures (Nom)	4000 h
Nominal Lifetime (Nom)	4000 h
Switching Cycle	16000X

##### Light Technical

Beam Angle (Nom)	36 °
Luminous Flux (Nom)	430 lm
Luminous Intensity (Max)	1000 cd
Rated Beam Angle	36 °
Correlated Color Temperature (Nom)	3000 K
Color Rendering Index (Nom)	100
Luminous Flux in 90° Cone (Rated)	430 lm

##### Operating and Electrical

Power (Rated) (Nom)	35 W
Starting Time (Nom)	0.0 s
Warm Up Time to 60% Light (Nom)	instant full light s

Voltage (Nom)	12 V
---------------	------

##### Controls and Dimming

Dimmable	Yes
----------	-----


##### Approval and Application

Energy Efficiency Label (EEL)	B
Energy Consumption kWh/1000 h	37 kWh

##### Product Data

Full product code	871869658842000
Order product name	Accentline 35W 4000h GU5.3 12V 36D 1CT/10X5F
EAN/UPC - Product	8718696588420
Order code	926000850062
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	926000850062
Net Weight (Piece)	0.032 kg

Dimensional drawing



Product	D (max)	C (max)
Accentline 35W 4000h GU5.3 12V 36D 1CT/10X5F	51 mm	46 mm

MR16 4000h 12V 35W 36D GU5.3

Photometric data

