



Halogen Clickline G9

Halogen MV Click 42W G9 230V CL 1CT


Ideal solution for small decorative luminaires. UV-block glass and safety fuse allow usage without cover glass. The compact Clickline gives crisp white light over a long lifetime.

Product data

General Information		Controls and Dimming	
Cap-Base	G9 [G9]	Dimmable	Yes
Operating Position	UNIVERSAL [Any or Universal (U)]		
Nominal Lifetime (Nom)	2000 h	Mechanical and Housing	
Switching Cycle	8000X	Bulb Finish	Clear
Light Technical		Approval and Application	
Luminous Flux (Nom)	630 lm	Energy Efficiency Label (EEL)	D
Luminous Flux (Rated) (Nom)	630 lm	Energy Consumption kWh/1000 h	42 kWh
Correlated Color Temperature (Nom)	2800 K	Luminaire Design Requirements	
Luminous Efficacy (Rated) (Nom)	15 lm/W	Bulb Temperature (Max)	950 °C
Color Rendering Index (Nom)	100	Pinch Temperature (Max)	350 °C
LLMF at End of Nominal Lifetime (Min)	80 %	Product Data	
Operating and Electrical		Full product code	872790086401400
Power (Rated) (Nom)	42.0 W	Order product name	Halogen MV Click 42W G9 230V CL 1CT
Lamp Current (Nom)	0.18 A	EAN/UPC - Product	8727900864014
Wattage Equivalent	60 W	Order code	925640844205
Starting Time (Nom)	0.0 s	Numerator - Quantity Per Pack	1
Warm Up Time to 60% Light (Nom)	instant full light	Numerator - Packs per outer box	100
Power Factor (Nom)	1	Material Nr. (12NC)	925640844205
Voltage (Nom)	230 V	Net Weight (Piece)	3.300 g

Halogen Clickline G9

Dimensional drawing



Product	D (max)	L	C (max)
Halogen MV Click 42W G9 230V CL 1CT	13 mm	21.7 mm	45 mm

CLICKLINE 42W G9 230V CL

