

# PHILIPS

# Lighting



## Capsuleline

### Capsuleline 35W GY6.35 12V CL 4000h 1CT/10X10F

Low-voltage halogen capsule. Ideal solution for small decorative luminaires. UV-block glass and low-pressure filling allow usage without cover glass. The compact Capsuleline delivers crisp white light over a long lifetime.

#### Product data

General Information	
Cap-Base	GY6.35 [ GY6.35]
Philips Code	13103
Operating Position	UNIVERSAL [ Any or Universal (U)]
Nominal Lifetime (Nom)	4000 h
Switching Cycle	16000X

Light Technical	
Luminous Flux (Nom)	600 lm
Luminous Flux (Rated) (Nom)	600 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (Rated) (Nom)	17 lm/W
Color Rendering Index (Nom)	100
LLMF at End of Nominal Lifetime (Min)	80 %

Operating and Electrical	
Power (Rated) (Nom)	35.0 W
Lamp Current (Nom)	2.95 A
Starting Time (Nom)	0.0 s
Warm Up Time to 60% Light (Nom)	instant full light
Power Factor (Nom)	1
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear
Cap-Base Information	15

Approval and Application	
Energy Efficiency Label (EEL)	C
Energy Consumption kWh/1000 h	37 kWh

Luminaire Design Requirements	
Bulb Temperature (Max)	900 °C
Pinch Temperature (Max)	350 °C


  

Product Data	
Full product code	871150040218950
Order product name	Capsuleline 35W GY6.35 12V CL 4000h 1CT/10X10F
EAN/UPC - Product	8711500402189
Order code	924040317101
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	100
Material Nr. (12NC)	924040317101

## Capsuline

Net Weight (Piece)	2.300 g
ILCOS Code	HSG/C/UB-35-12-GY6.35

### Dimensional drawing



CAP SU 13103 35W GY6.35 12V CL

Product	D (max)	L	C (max)
Capsuline 35W GY6.35 12V CL 4000h 1CT/10X10F	12 mm	30 mm	44 mm

