



Standard Extra Low Voltage A60

Standard ELV 60W E27/BRC 24V A60 CL 1CT/20

Clear lamp (A-bulb) for operation on voltages of 12, 24, 42 and 50 V

Product data


General Information			
Cap-Base	E27 [E27]		
Operating Position	UNIVERSAL [Any or Universal (U)]		
Nominal Lifetime (Nom)	1000 h		
Switching Cycle	4000X		
Light Technical			
Luminous Flux (Nom)	970 lm		
Luminous Flux (Rated) (Nom)	970 lm		
Correlated Color Temperature (Nom)	2700 K		
Color Rendering Index (Nom)	100		
Operating and Electrical			
Power (Rated) (Nom)	60.0 W		
Starting Time (Nom)	0.0 s		
Warm Up Time to 60% Light (Nom)	instant full light		
Voltage (Nom)	24 V		
Controls and Dimming			
Dimmable	Yes		

Mechanical and Housing			
Bulb Finish	Clear		
Cap-Base Information	Brass Cap		
Approval and Application			
Energy Efficiency Label (EEL)	D		
Energy Consumption kWh/1000 h	60 kWh		
Product Data			
Full product code	871150009018805		
Order product name	Standard ELV 60W E27/BRC 24V A60 CL 1CT/20		
EAN/UPC - Product	8711500090188		
Order code	920021020517		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	20		
Material Nr. (12NC)	920021020517		
Net Weight (Piece)	28.000 g		
ILCOS Code	IAA/C-60-24-E27-60		

Datasheet, 2017, November 6 data subject to change

Standard Extra Low Voltage A60

Dimensional drawing



ELV 60W E27/BRC 24V A60 CL

Product	D (max)	C (max)
Standard ELV 60W E27/BRC 24V A60 CL 1CT/20	60 mm	107.5 mm

