



Tornado High Lumen

Tornado High Lumen 75W CDL E40 1CT/6

Energy saving lamp in spiral shape, with superior performance (long life, high switching) and high lumen warm bright light. Perfectly suitable to be used in places where high lumen is required, and the lamp is directly visible.

Product data


General Information		Starting Time (Nom)	
Cap-Base	E40 [E40]		1.5 s
Nominal Lifetime (Nom)	10000 h	Warm Up Time to 60% Light (Max)	60 s
Switching Cycle	10000X	Power Factor (Nom)	0.92
		Voltage (Nom)	220-240 V
Light Technical		Controls and Dimming	
Color Code	865 [CCT of 6500K]	Dimmable	No
Luminous Flux (Nom)	5550 lm		
Luminous Flux (Rated) (Nom)	5550 lm	Approval and Application	
Color Designation	Cool Daylight	Energy Efficiency Label (EEL)	A
Lumen Maintenance 2000 h (Nom)	88 %	Mercury (Hg) Content (Max)	5 mg
Chromaticity Coordinate X (Nom)	313	Energy Consumption kWh/1000 h	75 kWh
Chromaticity Coordinate Y (Nom)	337	Product Data	
Correlated Color Temperature (Nom)	6500 K	Full product code	872790080723300
Luminous Efficacy (Rated) (Nom)	73.96 lm/W	Order product name	Tornado High Lumen 75W CDL E40 1CT/6
Color Rendering Index (Nom)	80	EAN/UPC - Product	8727900807233
LLMF At End Of Nominal Lifetime (Nom)	60 %	Order code	929676006501
Operating and Electrical		Numerator - Quantity Per Pack	1
Input Frequency	50 or 60 Hz	Numerator - Packs per outer box	6
Power (Rated) (Nom)	75.0 W	Material Nr. (12NC)	929676006501
Lamp Current (Nom)	350 mA	Net Weight (Piece)	0.360 kg
Wattage Equivalent	340 W		

Tornado High Lumen

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Dimensional drawing



Product	C (max)	F (max)	D (max)
Tornado High Lumen 75W CDL E40 1CT/6	293 mm	88.1 mm	102 mm

HL HS HV 10Kh EMI HPF 80W 220-240VE40CDL

