

## Electrical data

### Power Supply

W210 / WIP 210 / WIP 220 / WIP 230

5VDC/1A Mini-USB connector

AC/DC adapter (110/230VAC/50-60 Hz) available (WPS100)

WIP 620 / WIP 630 / WIP 720 / WIP730

12VDC/1A - Wire connection

### Backup battery

Battery technology Rechargeable 3.7V Lithium-ion battery

Battery voltage (Fully charged) 4.1 V

Low battery level 3.95 V

Guaranteed autonomy when the low battery level is reached 36h

Average current consumption in standby mode 600 µA

Max consumption 1 A

### RF S2View® technology

Radio type Bidirectionnal RF

Operating frequency

868MHz - WIP210/220/230 - W210 (Europe, South Africa, Asia)

915MHz - FHSS - WIP620/630 (USA, Canada, South America)

920MHz - FHSS - WIP720/730 (Australia, South America)

Transmission security AES encryption algorithm

Radio jam detection Yes

Supervision Yes

Antenna Integrated

### Tamper Detection

Tamper Wall and cover tamper detection

## Box

### Physical and Environmental Data

Operating temperature -10°/+55°C

Maximum relative humidity 75%, non-condensing

Material ABS—ULV0

International Protection Marking IP31 / IK06

### Dimensions

Panel 143 mm x 200 mm x 44mm (LxWxD)

### Installation/Mounting

Control Panel/Base

Two screws secures control panel cover to base; Three screws secure control panel base to the wall

## Transmission

### Communicator

Communicator type 2G & LAN Ethernet (WIP210)

2G (W210)

LAN Ethernet (WIP220 / WIP620 / WIP720)

3G & LAN Ethernet (WIP230 / WIP630 / WIP730)

Security protocol Frontel

IP Stack TCP/IP

Video transmission By Frontel protocol to central monitoring station or App servers

2G3G Antenna Integrated

### Optional modules

Wi-Fi WWB100 (WLAN 802.11 b/g/n)

Wired Input/Outputs WIO100 (out of NF&A2P compliance)

Wired Siren WIS100

### Video

Video format WMV or MPEG

Images per second 5

Image size 320x240 or 640x480 pixels

Video length 4 to 12 seconds

### Miscellaneous

Programming Keypad or USB

Max number of devices 24

Max number of codes/badges 50

Arming modes 4

Areas 4

Event log 4,000 events stored on flash memory

### EMEA SALES

23, avenue du Général Leclerc

92340 BOURG-LA-REINE

FRANCE

E-Mail : emeasales@rsivideotech.com

### North American Headquarters

1375 Willow Lake Blvd, Suite 103

Vadnais Heights, MN 55110

USA

E-Mail : usasales@rsivideotech.com

