

230V 50Hz, copper windings, without thermal protection

Product name	Ordering code	Power [W]	Lamps	Lamp current [A]	ΔT [°C]	Thermal protection	Tw [°C]	Weight [kg]	Capacitor [μF]	EEI	Dimensions [mm]				
											A1	A2	B1	C1	D1
BHL 125 K202 230V 50Hz BC1-118	9137 002 85946	125	HPL	1,15	85	no	140	1,15	10	A3	118	94	61	52	6,2

230V 50Hz, aluminium windings, with thermal protection, EEI A2 class

Product name	Ordering code	Power [W]	Lamps	Lamp current [A]	ΔT [°C]	Thermal protection	Tw [°C]	Weight [kg]	Capacitor [μF]	EEI	Dimensions [mm]				
											A1	A2	B1	C1	D1
BHL 250 K202-A2-TS-A 230V 50Hz BC2-151	1010 109 19246	250	HPL/HPI	2,13/2,15	85	yes	140	2,25	18	A2	151	129	76	65	6,2
BHL 400 K202-A2-TS-A 230V 50Hz BC3-166	1010 109 19646	400	HPL/HPI	3,25/3,40	75/80	yes	140	4,34	25/28	A2	166	145	97	83	6,2

230V 50Hz, aluminium windings, without thermal protection, EEI A2 class

Product name	Ordering code	Power [W]	Lamps	Lamp current [A]	ΔT [°C]	Thermal protection	Tw [°C]	Weight [kg]	Capacitor [μF]	EEI	Dimensions [mm]				
											A1	A2	B1	C1	D1
BHL 250 K202-A2-A 230V 50Hz BC2-151	1010 109 13446	250	HPL/HPI	2,13/2,15	85	no	140	2,55	18	A2	151	129	76	65	6,2
BHL 400 K202-A2-A 230V 50Hz BC3-166	1010 109 13546	400	HPL/HPI	3,25/3,40	75/80	no	140	4,34	25/28	A2	166	145	97	83	6,2

230V 50Hz, aluminium windings, without thermal protection

Product name	Ordering code	Power [W]	Lamps	Lamp current [A]	ΔT [°C]	Thermal protection	Tw [°C]	Weight [kg]	Capacitor [μF]	EEI	Dimensions [mm]				
											A1	A2	B1	C1	D1
BHL 50 K202-A 230V 50Hz BC1-118	1010 109 13146	50	HPL	0,61	80	no	140	1,00	7	A3	118	94	61	52	6,2
BHL 80 K202-A 230V 50Hz BC1-118	1010 109 13246	80	HPL	0,80	85	no	140	1,00	7	A3	118	94	61	52	6,2
BHL 125 K202-A 230V 50Hz BC1-123	1010 109 13346	125	HPL	1,15	85	no	140	1,22	10	A3	123	98	61	52	6,2

230/240V 50Hz, copper windings, with thermal protection, EEI A2 class

Product name	Ordering code	Power [W]	Lamps	Lamp current [A]	ΔT [°C]	Thermal protection	Tw [°C]	Weight [kg]	Capacitor [μF]	EEI	Dimensions [mm]				
											A1	A2	B1	C1	D1
BHL 250 K307-A2-TS 230/240V 50Hz BC2-134	1010 109 19146	250	HPL/HPI	2,13/2,15	80/85	yes	140	2,25	18	A2	134	113	76	65	6,2
BHL 400 K307-A2-TS 230/240V 50Hz BC2-160	1010 109 19546	400	HPL/HPI	3,25/3,40	80/85	yes	140	3,24	25/28	A2	160	139	76	65	6,2

230/240V 50Hz, copper windings, without thermal protection, EEI A2 class

Product name	Ordering code	Power [W]	Lamps	Lamp current [A]	ΔT [°C]	Thermal protection	Tw [°C]	Weight [kg]	Capacitor [μF]	EEI	Dimensions [mm]				
											A1	A2	B1	C1	D1
BHL 250 K307-A2 230/240V 50Hz BC2-134	9137 002 78046	250	HPL/HPI	2,13/2,15	80/85	no	140	2,25	18	A2	134	113	76	65	6,2
BHL 400 K307-A2 230/240V 50Hz BC2-160	9137 002 78246	400	HPL/HPI	3,25/3,40	80/85	no	140	3,24	25/28	A2	160	139	76	65	6,2

230/240V 50Hz, copper windings, without thermal protection

Product name	Ordering code	Power [W]	Lamps	Lamp current [A]	ΔT [°C]	Thermal protection	Tw [°C]	Weight [kg]	Capacitor [μF]	EEI	Dimensions [mm]				
											A1	A2	B1	C1	D1
BHL 50/80 K407 230/240V 50Hz BC1-118	9137 002 86146	50/80	HPL	0,61/0,80	55/80	no	140	0,96	7	A3	118	94	61	52	6,2
BHL 80/125 K407 230/240V 50Hz BC1-118	9137 002 80246	80/125	HPL	0,80/1,15	50/80	no	140	1,23	7/10	A3	118	94	61	52	6,2
BHL 125 K307 230/240V 50Hz BC1-118	9137 002 86046	125	HPL	1,15	85	no	140	1,15	10	A3	118	94	61	52	6,2

220V 60Hz, copper windings, without thermal protection

Product name	Ordering code	Power [W]	Lamps	Lamp current [A]	ΔT [°C]	Thermal protection	Tw [°C]	Weight [kg]	Capacitor [μF]	EEI	Dimensions [mm]				
											A1	A2	B1	C1	D1
BHL 125 K201 220V 60Hz BC1-118	9137 002 87946	125	HPL	1,15	85	no	140	0,93	9	A3	118	94	61	52	6,2
BHL 250 K201 220V 60Hz BC2-126	9137 002 98046	250	HPL/HPI	2,13/2,15	85	no	140	1,95	15	A3	126	104	76	65	6,2
BHL 400 K201 220V 60Hz BC2-151	9137 002 87846	400	HPL/HPI	3,25/3,40	80/85	no	140	2,85	20/23	A3	151	129	76	65	6,2