



Capsuleline

Capsuleline 20W G4 12V CL 2000h 1CT/10X10F

Low-voltage halogen capsule. Ideal solution for small decorative luminaires. UV-block glass and low-pressure filling allow usage without cover glass. The compact Capsuleline delivers crisp white light over a long lifetime.

Product data

General Information	
Cap-Base	G4 [G4]
Philips Code	14729
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal Lifetime (Nom)	2000 h
Switching Cycle	8000X

Light Technical	
Luminous Flux (Nom)	255 lm
Luminous Flux (Rated) (Nom)	255 lm
Correlated Color Temperature (Nom)	2800 K
Luminous Efficacy (Rated) (Nom)	12.5 lm/W
Color Rendering Index (Nom)	100
LLMF at End of Nominal Lifetime (Min)	80 %

Operating and Electrical	
Power (Rated) (Nom)	20.0 W
Lamp Current (Nom)	1.67 A
Starting Time (Nom)	0.0 s
Warm Up Time to 60% Light (Nom)	instant full light
Power Factor (Nom)	1
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear
Cap-Base Information	-

Approval and Application	
Energy Efficiency Label (EEL)	C
Energy Consumption kWh/1000 h	21 kWh


Luminaire Design Requirements	
Bulb Temperature (Max)	220 °C
Pinch Temperature (Max)	350 °C

Product Data	
Full product code	871150041299750
Order product name	Capsuleline 20W G4 12V CL 2000h 1CT/10X10F
EAN/UPC - Product	8711500412997
Order code	924892017111
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	100
Material Nr. (12NC)	924892017111

Capsuleline

Net Weight (Piece)	0.001 kg
ILCOS Code	HSG/C/UB-20-12-G4

Dimensional drawing



CAP Fighter 14729 20W G4 12V CL

Product	D (max)	L	C (max)
Capsuleline 20W G4 12V CL 2000h 1CT/10X10F	10 mm	22 mm	33 mm

