

## RefLED ES111 DIM

RefLED ES111 1000LM DIM 830 25°SL

0027636



### Product features

- Energy saving replacement for halogen ES111 GU10 lamps • High lumen output - 1000lm • Compact design, same diameter as the halogen lamp • Stippled lens to help reduce glare and recreate the halogen light effect • 25° beam angle • High lumen intensity - 4500 cd • 90% energy saving - A+ EEl rating • 11.5 W equivalent to 122W • Dimmable • 25,000 H average rated life, last 12.5 times longer than halogen alternatives • 0.90 power factor • > 50,000X switching cycle • High lumen efficacy -87 lm/W • CRI 80



### NOTES

undefined

### PRODUCT OVERVIEW

IPC Code	0027636
Product name	RefLED ES111 1000LM DIM 830 25°SL
Technology	LED
Watt (Rated) (W)	11.5
Lamp shape	ES111
Cap/Base	GU10
Fixture rating	Open
General application	Hospitality, Retail, Residential & Consumer, Museums & Galleries,
Certifications	EUTIE111
ETIM Class	EC001959
E-number FI	4740563
E-number SE	8292815
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Beam Angle (°)	25
Wattage (W)	11.5
Product Voltage (V)	230
Average life (Nominal) (h)	25000
Product EAN number	5410288276366

### DATA TABLE

#### General data

IPC Code	0027636
Product name	RefLED ES111 1000LM DIM 830 25°SL
Technology	LED

## RefLED ES111 DIM

RefLED ES111 1000LM DIM 830 25°SL

0027636

Watt (Rated) (W)	11.5
Lamp shape	ES111
Cap/Base	GU10
Fixture rating	Open
General application	Hospitality, Retail, Residential & Consumer, Museums & Galleries,
Operating Temperature Range (°C)	25
Certifications	EUTIE111
ETIM Class	EC001959
E-number FI	4740563
E-number SE	8292815

### Optical data

Colour temperature (K)	3000
Light colour	Warm White
Colour Code	830
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Adjustable chromaticity	N
Beam Angle (°)	25
Beam angle (Rated) (°)	25

### Electrical data

Wattage (W)	11.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	2
Current (A)	55
Mains voltage (V)	220-240V~
Product Voltage (V)	230
Lamp power factor	0.9
No. Of switching cycles before premature failures	50000
Transformer required	Yes
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	12
Nominal Frequency (Hz)	50/60Hz

### Lifetime data

Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

### Physical data

Nominal Product Length (mm)	65
Nominal Product Diameter (mm)	111
Weight (kg)	0.155

### Packaging

Single packaging type	Carton
-----------------------	--------

## RefLED ES111 DIM

*RefLED ES111 1000LM DIM 830 25°SL*

0027636

Product EAN number	5410288276366
Packaging single length / height (cm)	11.5
Packaging single width (cm)	11.5
Packaging single depth (cm)	7.8
DUN14 (inner)	25410288276360
Units per inner package	6
Packaging inner length / height (cm)	36.5
Packaging inner width (cm)	12.5
Packaging inner depth (cm)	17.0
DUN14 (outer)	15410288276363
Units per outer package	24
Packaging outer length / height (cm)	38.3
Packaging outer width (cm)	27.0
Packaging outer depth (cm)	36.5

### Safety data

Breakage cleaning instructions	0
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

## RefLED ES111 DIM

RefLED ES111 1000LM DIM 830 25°SL

0027636

