



MASTER VALUE LEDs pot LV



MASTER LED spot VLE D 5.8-35W MR16 940 36D

Philips MASTER VALUE MR16 is the series of Low Voltage (12VAC) Halogen MR16 replacements. Not only does it employs Philips' patented solution to guarantee the broadest possible compatibility with standard 12V Halogen electronic transformers. It also delivers beam intensity which is equivalent to the 50W Philips Halogen MR16 lamps. The form-factor of Philips MASTER Value LED MR16 guarantees a 100% form on the back-side of the lamp (exact form with Halogen lamps.)

Warnings and Safety

- · Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- · Not intended for use with emergency light fixtures or exit lights

Product data

General information	
Cap-Base	GU5.3 [GU5.3]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	25000 h
Switching Cycle	50000X
Flux measurement reference	Narrow Cone
Light technical	
Color Code	940 [CCT of 4000K]
Beam Angle (Nom)	36°
Luminous Flux (Nom)	490 lm
Luminous Intensity (Nom)	1200 cd
Color Designation	Cool White (CW)
	· · · · · · · · · · · · · · · · · · ·

Correlated Color Temperature (Nom)	4000 K	
Luminous Efficacy (rated) (Nom)	84.00 lm/W	
Color Consistency	<6	
Color Rendering Index (Nom)	90	
LLMF At End Of Nominal Lifetime (Nom) 70 %		
Luminous Flux in 90° Cone (Rated)	490 lm	
Operating and electrical		
Input Frequency	- Hz	
Power (Nom)	5.8 W	
Lamp Current (Nom)	510 mA	
Wattage Equivalent	35 W	
Starting Time (Nom)	0.5 s	


Datasheet, 2022, July 28 data subject to change

MASTER VALUE LEDspot LV

Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.7
Voltage (Nom)	ac electronic 12 V
Temperature	
T-Case Maximum (Nom)	85 ℃
Controls and dimming	
Dimmable	Only with specific dimmers
Mechanical and housing	
Bulb Shape	MR16 [2inch/50mm]
	<u> </u>
Approval and application	·
Energy Efficiency Class	F
Suitable For Accent Lighting	Yes

6 kWh
453175
871951430722300
MASTER LED spot VLE D 5.8-35W MR16 940
36D
8719514307223
929002492702
1
10
929002492702
0.045 kg


Dimensional drawing




MASTER LED spot VLE D 5.8-35W MR16 940 36D



Photometric data




LEDspots MAS 5,8W MR16 GU5,3 940 36D



LEDspots MAS 5,8W MR16 GU5,3 940 36D

MASTER VALUE LEDspot LV


Photometric data




Calculus Photometrics 4.5 Philips Lighting B.V. Fago: 171

LEDspots MAS 5,8W MR16 GU5,3 940 36D

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.