

Softone Lustre

Softone Lustre 5W WW E14 220-240V 1PF

Extremely compact covered energy saving lamp that produces soft and gentle decorative light, complementing any luminaries

Product data

• General Characteristics

Cap-Base E14
Bulb P52
Nominal Lifetime 10000 hr
Rated Lifetime 10000 hr
(hours)
Rated Lifetime 10 an

(years)

Color Code

• Light Technical Characteristics

Color Rendering 81 (min) Ra8 Index Warm White Color Designation (text) 2700 K Color Temperature Color Temperature 2700 K Technical 195 Lm Luminous flux lamp Rated Luminous Flux 195 Lm Luminous Efficacy 38 Lm/W Lamp Lumen Maintenance 83 % 2000h Lumen Maintenance 70 % 6000h LLMF - end nominal 65 % lifetime Chromaticity Coor-463 dinate X Chromaticity Coor-420 dinate Y

827 [CCT of 2700K]

• Electrical Characteristics

Rated Wattage 5.0 W

Lamp Wattage 5 W Power Factor 0.6 -220-240 V Voltage Lamp Current mA 40 mA Line Frequency 50/60 Hz Dimmable . No 22 W Wattage Equivalent 1.5 s Starting Time Warm-up Time to 10 (min), 80 (max) s

60% Light Outp

• Environmental Characteristics

Energy Efficiency A Label (EEL)

Mercury (Hg) 1.5 (nom), 2.0 (max) mg

Content

Energy consumption

kWh/1000h

• Measuring Conditions

Switching cycle 30000X

• Product Dimensions

 Overall Length C
 89.5 (max) mm

 Diameter D
 53.5 (max) mm

 Width F
 48.5 (max) mm

• Product Data

Order code 929689130104
Full product code 929689130104
Full product name Softone Lustre 5W WW E14
220-240V 1PF

5 kWh



Softone Lustre

Order product name Softone Lustre 5W WW E14

220-240V 1PF/6

Pieces per pack 1
Packing configuration 6
Packs per outerbox 6

Bar code on pack - 8718291657927

EAN1

Warnings and Safety

 Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic Bar code on 8718291657934

outerbox - EAN3

Logistic code(s) - 929689130104


12NC

Net weight per piece 0.050 kg

bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Compact fluorescent lamps have to be treated as special waste, they
must be taken to your local waste facilities for recycling. The
European Lighting Industry has set up an infrastructure, capable of
recycling mercury, other metals, glass etc.

Dimensional drawing



Softone Lustre 5W WW E14 220-240V 1PF

Product	C (Max)	D (Max)	F (Max)
Luster Erp 5W/827 E14 220-240V 50/60Hz	89.5	53.5	48.5



E14



© 2013 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.