

MASTERCcolour CDM-TC

MASTERCcolour CDM-TC - 70W/842 G8.5 1CT

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light



Product data

• General Characteristics

Cap-Base	G8.5
Bulb	T14 [T 14 mm]
Bulb Material	UV-Block Quartz
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Life to 5% failures EL	6000 hr
Life to 10% failures EL	8000 hr
Life to 20% failures EL	9000 hr
Life to 50% failures EL	12000 hr

• Light Technical Characteristics

Color Code	842 [CCT of 4200K]
Color Rendering Index	86 (min), 89 (nom) Ra8
Color Designation (text)	Cool White
Color Temperature	4200 K
Color Temperature Technical	4200 K
Luminous Flux Lamp EL	5900 Lm
Luminous Efficacy Lamp EL	80 Lm/W
Lumen Maintenance EL 2000h	80 %
Lumen Maintenance EL 5000h	75 %
Lumen Maintenance EL 10000h	65 %
Design Mean Lumens EL	4300 Lm

Chromaticity Coordinate X	0.362 -
Chromaticity Coordinate Y	0.363 -

• Electrical Characteristics

Lamp Wattage	70 W
Lamp Wattage EL 25°C, Rated	73.0 W
Lamp Wattage EL 25°C, Nominal	70.0 W
Lamp Voltage	88 V
Lamp Current EL	0.830 A
Ignition Time	30 (max) s
Run-up time 90%	3 (max) min
Re-ignition Time [min]	15 (max) min
Dimmable	No

• Environmental Characteristics

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content	7 mg
Energy consumption kWh/1000h	80 kWh

• UV-related Characteristics

• Luminaire Design Requirements

Pinch Temperature	300 (max) C
Bulb Temperature	700 (max) C

PHILIPS

• Product Dimensions

Overall Length C	85 (max) mm
Diameter D	15 (max) mm
Light Center Length L	51 (min), 52 (nom), 53 (max) mm
Arc Length O	5 mm
Light Center Length L [inch]	2 in
Overall Length C [inch]	3.34375 (max) in

• Product Data

Order code	928094605131
Full product code	928094605131


Full product name	MASTERC colour CDM-TC - 70W/842 G8.5 1CT
Order product name	MASTERC CDM-TC - 70W/842 G8.5 1CT/12
Pieces per pack	1
Packing configuration	12
Packs per outerbox	12
Bar code on pack - EAN1	8711500212757
Bar code on outerbox - EAN3	8711500212764
Logistic code(s) - 12NC	928094605131
ILCOS code	MT/UB-70/842-H-G8.5-17/85
Net weight per piece	0.010 kg

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures


- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. 35W/830 lamps may also use electromagnetic gear.

Dimensional drawing




MASTERC colour CDM-TC - 70W/842 G8.5 1CT

Product	C (Max)	D (Max)	L (Min)	L (Norm)	L (Max)	O (Norm)
CDM-TC 70W/842 G8.5	85	15	51	52	53	5



G8.5

Photometric data



© 2013 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2013, October 9
data subject to change