



MASTERCcolour CDM-T Warm

MASTERCcolour CDM-T Warm 70W/925 G12

The world's most efficient and lowest-cost accent lighting is to become available in highly efficient sparkling warm light. CDM Warm is the only light source that combines very warm light with near-perfect color rendering and very high efficacy.

Product data

• General Characteristics

Cap-Base	G12
Bulb	T19 [T 19mm]
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Life to 5% failures EL	7000 hr
Life to 10% failures EL	8000 hr
Life to 20% failures EL	10000 hr
Life to 50% failures EL	15000 hr

• Light Technical Characteristics

Color Code	925
Color Rendering Index	93 Ra8
Color Designation (text)	Warm
Color Temperature	2600 K
Color Temperature Technical	2640 K
Luminous Flux Lamp EL	6500 Lm
Luminous Efficacy Lamp EL	89 Lm/W
Lumen Maintenance EL 2000h	94 %
Lumen Maintenance EL 4000h	90 %
Lumen Maintenance EL 5000h	88 %
Lumen Maintenance EL 10000h	83 %
Lumen Maintenance EL 12000h	82 %

Lumen Maintenance EL 15000h	80 %
Chromaticity Coordinate X	0.460 -
Chromaticity Coordinate Y	0.405 -

• Electrical Characteristics

Lamp Wattage	70 W
Lamp Wattage EL 25°C, Rated	73.0 W
Lamp Wattage EL 25°C, Nominal	70.0 W
Lamp Voltage	95 V
Lamp Current EL	0.77 A
Ignition Time	30 (max) s
Run-up time 90%	3 (max) min
Re-ignition Time [min]	15 (max) min
Dimmable	No

• Environmental Characteristics

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content	8.6 mg
Energy consumption kWh/1000h	80 kWh

• UV-related Characteristics

PET (NIOSH)	1000 h.klx
Damage Factor D/fc	0.1 -

PHILIPS

MASTERColour CDM-T Warm

• Luminaire Design Requirements

Cap-Base Temperature	250 (max) C
Pinch Temperature	350 (max) C
Bulb Temperature	500 (max) C

• Product Dimensions

Overall Length C	103 (max) mm
Diameter D	20 (max) mm
Light Center Length L	55 (min), 56 (nom), 57 (max) mm
Arc Length O	5 mm
Light Center Length L [inch]	2.2 in
Overall Length C [inch]	3.94 (max) in
Diameter D [inch]	0.75 in

• Product Data


Order code	928061405131
Full product code	928061405131
Full product name	MASTERColour CDM-T Warm 70W/925 G12
Order product name	MASTERColour CDM-T Warm 70W/925 G12
Pieces per pack	1
Packing configuration	12
Packs per outerbox	12
Bar code on pack - EAN1	8718291203056
Bar code on outerbox - EAN3	8718291203063
Logistic code(s) - 12NC	928061405131
ILCOS code	MT/UB-70/925-H-G12-20/90
Net weight per piece	0.029 kg

Warnings and Safety


- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures

- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)

Dimensional drawing




G12



MASTERColour CDM-T Warm 70W/925 G12

Dimensional drawing

Product	C (Max)	D (Max)	L (Min)	L (Norm)	L (Max)	O (Norm)
CDM-T Warm 70W/925 G12	103	20	55	56	57	5



G12



© 2013 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2013, October 26
data subject to change