


Lynx-S

SA LYNX-S 11W/840 G23 SLV 10

0025891



Range Features

- Single pin-base compact lamps, suitable for wide range of applications
- Excellent colour rendering - (CRI=85)
- For use with magnetic ballast
- Available in Homelight (2700K), Warm White (3000K) and Cool white (4000K)
- Average rated life: 10000 hours



PRODUCT OVERVIEW

Lamp finish	frosted
Lamp shape	Stick
Colour temperature (K)	4000
CRI (Ra)	80
Dimmable	NO
EAN code	5410288258911
Energy class	A
Cap/Base	G23
Type	Lynx S
Watt (Nominal) (W)	11
Light colour	840 Cool White
Ordering number	0025891
Efficacy (Rated) (lm/w)	76
Average life (Rated) (h)	10000
Luminous flux (Rated) (lm)	900
Technology	Compact Fluorescent
Voltage (V)	91

DATA TABLE

Optical data

Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	4000
CRI (Ra)	80
Light colour	840 Cool White
Luminous flux (Nominal) (lm)	900
Rated lumen maint. factor at 12000 h 50Hz	0.8

Lynx-S

SA LYNX-S 11W/840 G23 SLV 10

0025891

Rated lumen maint. factor at 2000 h 50Hz	0.85
Rated lumen maint. factor at 4000 h 50Hz	0.78
Rated lumen maint. factor at 6000 h 50Hz	0.76
Rated lumen maint. factor at 8000 h 50Hz	0.75
Luminous flux (Rated) (lm)	900

General data

Average life (Nominal) (h)	10000
Control gear required	Yes
Lamp finish	frosted
Lamp shape	Stick
Dimmable	NO
Dry applications use only	yes
EAN code	5410288258911
Energy class	A
Fixture rating	Open
General application	Retail;Hospitality;Logistics and Industry;Museums;Education;Office;Residential & Consumer;
IEC Reference	IEC 60901
IEC Reference 2	IEC 61199
IEC Reference 3	IEC 60921
Intended purpose	General lighting
Cap/Base	G23
Lamp mercury content (mg)	< 2.50 mg
Type	Lynx S
Ordering number	0025891
Range features	Single pin-base compact lamps, suitable for wide range of applications Excellent colour rendering - (CRI=85) For use with magnetic ballast Available in Homelight (2700K), Warm White (3000K) and Cool white (4000K) Average rated life: 10000 hours
Product name	SA LYNX-S 11W/840 G23 SLV 10
Average life (Rated) (h)	10000
Rated survival factor at 12000 h 50Hz	0.62
Rated survival factor at 2000 h 50Hz	0.98
Rated survival factor at 4000 h 50Hz	0.9
Rated survival factor at 6000 h 50Hz	0.7
Rated survival factor at 8000 h 50Hz	0.50
Special purpose lamp	No

Lynx-S

SA LYNX-S 11W/840 G23 SLV 10

0025891

Starting time (max) (s)	10 Sec
Technology	Compact Fluorescent
Transformer required	No
Sales pack quantity	10
E-number SE	8357267
E-number FI	4944090


Electrical data

Current (A)	0.155
Ignition voltage (V)	186
kWh per 1000 hours burning time	14
Watt (Nominal) (W)	11
Efficacy (Rated) (lm/w)	76
Rated lamp efficacy (lm/W) 100H 50Hz at optimum temp.	76
Watt (Rated) (W)	11.8
Voltage (V)	91

Physical data

Max. Lamp Diameter (mm) - D	32.5
Lamp Length (mm) - C/L	213
Length base to base (mm) - A	236
Single packaging type	Box/Sleeve
Weight (kg)	0.04
Inner package net weight (kg)	0.38
Inner package dimensions (L x W x H) (cm)	12.40 x 9.00 x 24.80
Outer package dimensions (L x W x H) (cm)	45.50 x 26.90 x 26.50
Single package dimensions (L x W x H) (cm)	2.20 x 3.80 x 22.90

TECHNICAL DRAWINGS



Lynx-S

SA LYNX-S 11W/840 G23 SLV 10

0025891

