


## Lynx-S


SA LYNX-S 9W/840 G23 SLV 10 P

**0025890**



### Range Features

- Single pin-base compact lamps, suitable for wide range of applications
- Excellent colour rendering - (CRI=85)
- For use with magnetic ballast
- Available in Homelight (2700K), Warm White (3000K) and Cool white (4000K)
- Average rated life: 10000 hours



### PRODUCT OVERVIEW

Lamp finish	frosted
Lamp shape	Stick
Colour temperature (K)	4000
CRI (Ra)	80
Dimmable	NO
EAN code	5410288258904
Energy class	A
Cap/Base	G23
Type	Lynx S
Watt (Nominal) (W)	9
Light colour	840 Cool White
Ordering number	0025890
Efficacy (Rated) (lm/w)	67
Average life (Rated) (h)	10000
Luminous flux (Rated) (lm)	600
Technology	Compact Fluorescent
Voltage (V)	60

### DATA TABLE

#### Optical data

Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	4000
CRI (Ra)	80
Light colour	840 Cool White
Luminous flux (Nominal) (lm)	600
Rated lumen maint. factor at 12000 h 50Hz	0.8

## Lynx-S

SA LYNX-S 9W/840 G23 SLV 10 P

0025890

Rated lumen maint. factor at 2000 h 50Hz	0.85
Rated lumen maint. factor at 4000 h 50Hz	0.78
Rated lumen maint. factor at 6000 h 50Hz	0.76
Rated lumen maint. factor at 8000 h 50Hz	0.75
Luminous flux (Rated) (lm)	600

### General data

Average life (Nominal) (h)	10000
Control gear required	Yes
Lamp finish	frosted
Lamp shape	Stick
Dimmable	NO
Dry applications use only	yes
EAN code	5410288258904
Energy class	A
General application	Retail;Hospitality;Logistics and Industry;Museums;Education;Office;Residential & Consumer;
IEC Reference	IEC 60901
IEC Reference 2	IEC 61199
IEC Reference 3	IEC 60921
Intended purpose	General lighting
Cap/Base	G23
Lamp mercury content (mg)	< 2.50 mg
Type	Lynx S
Ordering number	0025890

### Range features

Single pin-base compact lamps, suitable for wide range of applications  
 Excellent colour rendering - (CRI=85)  
 For use with magnetic ballast  
 Available in Homelight (2700K), Warm White (3000K) and Cool white (4000K)  
 Average rated life: 10000 hours

Product name	SA LYNX-S 9W/840 G23 SLV 10 P
Average life (Rated) (h)	10000
Rated survival factor at 12000 h 50Hz	0.62
Rated survival factor at 2000 h 50Hz	0.98
Rated survival factor at 4000 h 50Hz	0.9
Rated survival factor at 6000 h 50Hz	0.7
Rated survival factor at 8000 h 50Hz	0.50
Special purpose lamp	No
Starting time (max) (s)	10 Sec

## Lynx-S

SA LYNX-S 9W/840 G23 SLV 10 P

**0025890**

<b>Technology</b>	Compact Fluorescent
<b>Transformer required</b>	No
<b>Sales pack quantity</b>	10
<b>E-number SE</b>	8357262
<b>E-number FI</b>	4944089


### Electrical data

<b>Current (A)</b>	0.17
<b>Ignition voltage (V)</b>	177
<b>kWh per 1000 hours burning time</b>	11
<b>Watt (Nominal) (W)</b>	9
<b>Efficacy (Rated) (lm/w)</b>	67
<b>Rated lamp efficacy (lm/W) 100H 50Hz at optimum temp.</b>	67
<b>Watt (Rated) (W)</b>	8.7
<b>Voltage (V)</b>	60

### Physical data

<b>Max. Lamp Diameter (mm) - D</b>	32.5
<b>Lamp Length (mm) - C/L</b>	145
<b>Length base to base (mm) - A</b>	168
<b>Single packaging type</b>	Box/Sleeve
<b>Weight (kg)</b>	0.03
<b>Inner package net weight (kg)</b>	0.26
<b>Inner package dimensions (L x W x H) (cm)</b>	12.20 x 8.80 x 18.00
<b>Outer package dimensions (L x W x H) (cm)</b>	45.50 x 26.10 x 19.50
<b>Single package dimensions (L x W x H) (cm)</b>	2.20 x 3.80 x 15.90

## TECHNICAL DRAWINGS



Lynx-S

SA LYNX-S 9W/840 G23 SLV 10 P

**0025890**

