



MASTER PL-L 4 Pin

MASTER PL-L 80W/840/4P 1CT

MASTER PL-L is a medium to high-wattage linear compact fluorescent lamp, typically used for general-illumination ceiling luminaires in retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. It is designed for operation on electromagnetic as well as electronic HF control gear and is provided with a plug-in/pull-out lamp base.

Product data

• General Characteristics

System Description	High Frequency [High Frequency]
Cap-Base	2G11
Cap-Base Information	4P
Life to 10% fail	14000 hr
Preheat EL,3h	
Life to 10% fail	7500 hr
Nonpreh EL,3h	
Life to 50% fail	20000 hr
Preheat EL,3h	
Life to 50% fail	10000 hr
Nonpreh EL,3h	
LSF HF Preheat	99 %
2000h Rated,3h	
LSF HF Preheat	99 %
4000h Rated,3h	
LSF HF Preheat	98 %
6000h Rated,3h	
LSF HF Preheat	97 %
8000h Rated,3h	
LSF HF Preheat	94 %
12000h Rated,3h	
LSF HF Preheat	82 %
16000h Rated,3h	
LSF HF Preheat	50 %
20000h Rated,3h	

• Light Technical Characteristics

Color Code	840 [CCT of 4000K]
Color Rendering Index	82 Ra8
Color Designation (text)	Cool White
Color Temperature	4000 K
Luminous Flux EL	6000 Lm
25°C, Rated	

Luminous Flux EL	6000 Lm
25°C, Nominal	
Lum Flux Rated HF	6000 Lm
25°C,horiz	
Lum Flux Nominal	6000 Lm
HF 25°C,horiz	
Lum Efficacy Rated	75 Lm/W
HF 25°C,hor	
LLMF HF 2000h	95 %
Rated	
LLMF HF 4000h	94 %
Rated	
LLMF HF 6000h	93 %
Rated	
LLMF HF 8000h	92 %
Rated	
LLMF HF 12000h	91 %
Rated	
LLMF HF 16000h	90 %
Rated	
LLMF HF 20000h	90 %
Rated	
Design Temperature	30 C
Chromaticity Coordinate X	380 -
Chromaticity Coordinate Y	380 -

• Electrical Characteristics

Lamp Wattage	80 W
Lamp Wattage EL	80.0 W
25°C, Rated	
Lamp Wattage EL	80 W
25°C, Nominal	
Lamp Voltage EL	145 V
25°C	



MASTER PL-L 4 Pin

Lamp Current EL 25°C 0.555 A
Dimmable Yes

Overall Length C 571.6 (max) mm
Diameter D 39.0 (max) mm
Diameter D1 18.0 (max) mm

• Environmental Characteristics

Energy Efficiency Label (EEL) A
Mercury (Hg) Content 2.0 mg
Energy consumption kWh/1000h 88

• Measuring Conditions

• Product Dimensions

Base Face to Base Face A 539.2 (max) mm
Insertion Length B 565 (max) mm

• Product Data


Order code 927909584070
Full product code 927909584070
Full product name MASTER PL-L 80W/840/4P 1CT
Order product name MASTER PL-L 80W/840/4P 1CT/25
Pieces per pack 1
Packing configuration 25
Packs per outerbox 25
Bar code on pack - EAN1 8711500867124
Bar code on outerbox - EAN3 8711500867131
Logistic code(s) - 12NC 927909584070
ILCOS code FSDH-80/40/1B-L/P-2G11
Net weight per piece 140.000 gr

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear

- Shorter lamp life when often switching and not well pre-heated electrodes

Dimensional drawing




2G11

MASTER PL-L 80W/840/4P 1CT

Product	A (Max)	B (Max)	C (Max)	D (Max)	D1 (Max)
PL-L 80W/840/4P HF	539.2	565	571.6	39.0	18.0

Photometric data



© 2013 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2013, June 27
data subject to change