

## PRODUCT INFORMATION SHEET

### SDS+ masonry drill bit




















































#### Description




Professional SDS plus drill bits designed for drilling in brick, stone, concrete and reinforced concrete. Drill bits accept all drills with an SDS-plus handle.

#### Characteristics

- 4x90° special geometry of tip makes drilling faster and reduces the risk of the drill jamming, even during work with reinforced bars
- blade made of high quality tungsten carbide
- double volute for fast evacuation of swarf and high efficiency
- centring tip facilitates an easier start to drilling
- SDS plus handle for fast drill bit changes

|   |  |  |
|--|---|---|
| ø 4.0  110 mm  50 mm   | HT6D201   | 5901867169266   |
| ø 5.0  110 mm  50 mm   | HT6D202   | 5901867169280   |
| ø 5.0  160 mm  90 mm   | HT6D203   | 5901867169303   |
| ø 6.0  110 mm  50 mm   | HT6D204   | 5901867169327   |
| ø 6.0  160 mm  90 mm   | HT6D205   | 5901867169365   |
| ø 6.0  210 mm  135 mm  | HT6D206   | 5901867169341   |
| ø 6.0  260 mm  185 mm  | HT6D207   | 5901867169389   |
| ø 8.0  160 mm  90 mm   | HT6D209   | 5901867169402   |
| ø 8.0  210 mm  135 mm  | HT6D210   | 5901867169426   |
| ø 10.0  160 mm  90 mm  | HT6D213   | 5901867169440   |
| ø 10.0  260 mm  185 mm | HT6D214   | 5901867169464   |
| ø 10.0  350 mm  280 mm | HT6D215   | 5901867169488   |
| ø 12.0  160 mm  90 mm  | HT6D218   | 5901867169501   |
| ø 12.0  260 mm  185 mm | HT6D220   | 5901867169525   |
| ø 12.0  600 mm  490 mm | HT6D224   | 5901867169549   |
| ø 14.0  260 mm  185 mm | HT6D226   | 5901867169563   |
| ø 14.0  600 mm  490 mm | HT6D231   | 5901867169587   |
| ø 16.0  260 mm  185 mm | HT6D233   | 5901867169600   |
| ø 16.0  600 mm  490 mm | HT6D236   | 5901867169624   |
| ø 18.0  260 mm  185 mm | HT6D237   | 5901867169648   |
| ø 18.0  600 mm  490 mm | HT6D240   | 5901867169662   |
| ø 20.0  600 mm  490 mm | HT6D242   | 5901867169686   |
| ø 24.0  600 mm  490 mm | HT6D248   | 5901867169709   |

#### Technical data

|   |  |
|---|--|
|  | 1 pc   |
|  | T6D231; HT6D236 - 10 pcs; HT6D237 - 15 pcs; HT6D242; HT6D248 - 5 pcs; HT6D240 - 10 pcs; HT6D203; HT6D205; HT6D209 - 60 pcs; HT6D215; HT6D233 - 25 pcs; HT6D224 - 20 pcs; HT6D226 - 40 pcs; HT6D201; HT6D202; HT6D204; HT6D206; HT6D207; HT6D210; HT6D213; HT6D214; HT6D218; HT6D220 - 50 pcs |
|  | YG6X tungsten carbide  |

